

Package: amadeus (via r-universe)

September 3, 2024

Title Accessing and Analyzing Large-Scale Environmental Data

Version 1.0.7

Maintainer Kyle Messier <kyle.messier@nih.gov>

Description Functions are designed to facilitate access to and utility with large scale, publicly available environmental data in R. The package contains functions for downloading raw data files from web URLs (`download_data()`), processing the raw data files into clean spatial objects (`process_covariates()`), and extracting values from the spatial data objects at point and polygon locations (`calc_covariates()`). These functions call a series of source-specific functions which are tailored to each data sources/datasets particular URL structure, data format, and spatial/temporal resolution. The functions are tested, versioned, and open source and open access. For `calc_sedc()` method details, see Messier, Akita, and Serre (2012) <[doi:10.1021/es203152a](https://doi.org/10.1021/es203152a)>.

Depends R (>= 4.1.0)

Imports dplyr, sf, sftime, stats, terra, methods, data.table, httr, rvest, exactextractr, utils, stringi, testthat (>= 3.0.0), parallelly, stars, future, future.apply, tidyr, rlang, nhdplusTools, archive, collapse, Rdpack

Suggests covr, withr, knitr, rmarkdown, lwgeom, FNN, doRNG, devtools, stringr, tigris, spelling

RdMacros Rdpack

Encoding UTF-8

VignetteBuilder knitr, rmarkdown

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Config/Needs/website tidyverse/tidytemplate

Config/testthat/edition 3

License MIT + file LICENSE

URL <https://niehs.github.io/amadeus/>

BugReports <https://github.com/NIEHS/amadeus/issues>

Language en-US

Repository <https://niehs.r-universe.dev>

RemoteUrl <https://github.com/niehs/amadeus>

RemoteRef HEAD

RemoteSha 541bd6898f9e9aa8890a39b95ea1268e25977615

Contents

as_mysftime	4
calc_covariates	5
calc_ecoregion	6
calc_geos	8
calc_gmted	9
calc_gridmet	10
calc_hms	12
calc_koppen_geiger	13
calc_lagged	14
calc_merra2	15
calc_modis_daily	17
calc_modis_par	18
calc_narr	21
calc_nei	22
calc_nlcd	23
calc_return_locs	25
calc_sedac_groads	26
calc_sedac_population	27
calc_sedc	28
calc_temporal_dummies	30
calc_terraclimate	31
calc_tri	32
check_mysf	34
check_mysftime	34
check_urls	35
check_url_status	35
download_aqs	36
download_cropscape	37
download_data	39
download_ecoregion	41
download_geos	42
download_gmted	44
download_gridmet	45
download_hms	46
download_huc	48

download_koppen_geiger	49
download_merra2	51
download_modis	59
download_narr	62
download_nei	63
download_nlcd	65
download_prism	66
download_sedac_groads	68
download_sedac_population	70
download_terraclimate	71
download_tri	73
dt_as_mysftime	74
generate_date_sequence	75
generate_time_sequence	75
narr_variable	76
process_aqs	76
process_blackmarble	78
process_blackmarble_corners	79
process_collection	80
process_conformity	81
process_covariates	81
process_cropscape	83
process_ecoregion	84
process_flatten_sds	85
process_geos	86
process_gmted	87
process_gmted_codes	88
process_gridmet	89
process_gridmet_codes	90
process_hms	90
process_huc	91
process_koppen_geiger	93
process_merra2	94
process_merra2_time	95
process_modis_merge	95
process_modis_sds	97
process_modis_swath	98
process_modis_warp	99
process_narr	101
process_nei	102
process_nlcd	103
process_prism	104
process_sedac_codes	105
process_sedac_groads	105
process_sedac_population	106
process_terraclimate	107
process_terraclimate_codes	108
process_tri	109

process_variable_codes	110
rename_time	111
sftime_as_mysftime	111
sftime_as_sf	112
sftime_as_spatraster	112
sftime_as_spatrds	113
sftime_as_spatvector	114
sf_as_mysftime	114
spatraster_as_sftime	115
spatrds_as_sftime	115
spatvector_as_sftime	116

Index	117
--------------	------------

as_mysftime	<i>Create an sftime object</i>
-------------	--------------------------------

Description

Create a sftime object from one of `data.frame`, `data.table`, `sf`, `sftime`, `SpatRaster`, `SpatRasterDataset`, `SpatVector`

Usage

```
as_mysftime(x, ...)
```

Arguments

<code>x</code>	an object of class <code>data.frame</code> , <code>data.table</code> , <code>sf</code> , <code>sftime</code> , <code>SpatRaster</code> , <code>SpatRasterDataset</code> or <code>SpatVector</code>
<code>...</code>	if <code>x</code> is a <code>data.frame</code> or <code>data.table</code> : <code>lonname</code> , <code>latname</code> , <code>timename</code> and <code>crs</code> arguments are required. If <code>x</code> is a <code>sf</code> or <code>sftime</code> , <code>timename</code> argument is required. If <code>x</code> is a <code>terra::SpatRaster</code> , <code>varname</code> argument is required.

Value

an sftime object with constrained time column name

Author(s)

Eva Marques

See Also

[check_mysftime](#), [sf_as_mysftime](#), [data.frame](#), [data.table::data.table](#), [terra::rast](#), [terra::sds](#), [terra::vect](#)

calc_covariates	<i>Calculate covariates wrapper function</i>
-----------------	--

Description

The `calculate_covariates()` function extracts values at point locations from a `SpatRaster` or `SpatVector` object returned from `process_covariates()`. `calculate_covariates()` and the underlying source-specific covariate functions have been designed to operate on the processed objects. To avoid errors, **do not edit the processed `SpatRaster` or `SpatVector` objects before passing to `calculate_covariates()`.**

Usage

```
calc_covariates(
  covariate = c("modis", "koppen-geiger", "koeppen-geiger", "koppen", "koeppen", "geos",
    "dummies", "gmted", "sedac_roads", "roads", "roads", "ecoregions", "ecoregion",
    "hms", "smoke", "gmted", "narr", "geos", "sedac_population", "population", "nlcd",
    "merra", "merra2", "gridmet", "terraclimate", "tri", "nei"),
  from,
  locs,
  locs_id = "site_id",
  ...
)
```

Arguments

<code>covariate</code>	character(1). Covariate type.
<code>from</code>	character. Single or multiple from strings.
<code>locs</code>	sf/SpatVector. Unique locations. Should include a unique identifier field named <code>locs_id</code>
<code>locs_id</code>	character(1). Name of unique identifier. Default is "site_id".
<code>...</code>	Arguments passed to each covariate calculation function.

Value

Calculated covariates as a `data.frame` or `SpatVector` object

Note

`covariate` argument value is converted to lowercase.

Author(s)

Insang Song

See Also

- `calc_modis_par`: "modis", "MODIS"
- `calc_koppen_geiger`: "koppen-geiger", "koeppen-geiger", "koppen"
- `calc_ecoregion`: "ecoregion", "ecoregions"
- `calc_temporal_dummies`: "dummies", "Dummies"
- `calc_hms`: "hms", "smoke", "HMS"
- `calc_gmted`: "gmted", "GMTED"
- `calc_narr`: "narr", "NARR"
- `calc_geos`: "geos", "geos_cf", "GEOS"
- `calc_sedac_population`: "population", "sedac_population"
- `calc_sedac_groads`: "roads", "groads", "sedac_groads"
- `calc_nlcd`: "nlcd", "NLCD"
- `calc_tri`: "tri", "TRI"
- `calc_nei`: "nei", "NEI"
- `calc_merra2`: "merra", "MERRA", "merra2", "MERRA2"
- `calc_gridmet`: "gridMET", "gridmet"
- `calc_terraclimate`: "terraclimate", "TerraClimate"

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_covariates(
  covariate = "narr",
  from = narr, # derived from process_covariates() example
  locs = loc,
  locs_id = "id",
  geom = FALSE
)

## End(Not run)
```

calc_ecoregion

Calculate ecoregions covariates

Description

Extract ecoregions covariates (U.S. EPA Ecoregions Level 2/3) at point locations. Returns a `data.frame` object containing `locs_id` and binary (0 = point not in ecoregion; 1 = point in ecoregion) variables for each ecoregion.

Usage

```
calc_ecoregion(from = NULL, locs, locs_id = "site_id", geom = FALSE, ...)
```

Arguments

from	SpatVector(1). Output of process_ecoregion .
locs	sf/SpatVector. Unique locs. Should include a unique identifier field named locs_id
locs_id	character(1). Name of unique identifier.
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Placeholders.

Value

a data.frame or SpatVector object with dummy variables and attributes of:

- attr(, "ecoregion2_code"): Ecoregion lv.2 code and key
- attr(, "ecoregion3_code"): Ecoregion lv.3 code and key

Author(s)

Insang Song

See Also

[process_ecoregion](#)

Examples

```
## NOTE: Example is wrapped in `\dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_ecoregion(
  from = ecoregion, # derived from process_ecoregion() example
  locs = loc,
  locs_id = "id",
  geom = FALSE
)

## End(Not run)
```

`calc_geos`*Calculate atmospheric composition covariates*

Description

Extract atmospheric composition values at point locations. Returns a data.frame object containing `locs_id`, date and hour, vertical pressure level, and atmospheric composition variable. Atmospheric composition variable column name reflects variable and circular buffer radius.

Usage

```
calc_geos(  
  from,  
  locs,  
  locs_id = NULL,  
  radius = 0,  
  fun = "mean",  
  geom = FALSE,  
  ...  
)
```

Arguments

<code>from</code>	SpatRaster(1). Output of <code>process_geos()</code> .
<code>locs</code>	data.frame, character to file path, SpatVector, or sf object.
<code>locs_id</code>	character(1). Column within locations CSV file containing identifier for each unique coordinate location.
<code>radius</code>	integer(1). Circular buffer distance around site locations. (Default = 0).
<code>fun</code>	character(1). Function used to summarize multiple raster cells within sites location buffer (Default = mean).
<code>geom</code>	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of <code>from</code> .
<code>...</code>	Placeholders.

Value

a data.frame or SpatVector object

Author(s)

Mitchell Manware

See Also

[process_geos\(\)](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_geos(
  from = geos, # derived from process_geos() example
  locs = loc,
  locs_id = "id",
  radius = 0,
  fun = "mean",
  geom = FALSE
)

## End(Not run)
```

calc_gmted

Calculate elevation covariates

Description

Extract elevation values at point locations. Returns a `data.frame` object containing `locs_id`, year of release, and elevation variable. Elevation variable column name reflects the elevation statistic, spatial resolution of `from`, and circular buffer radius (ie. Breakline Emphasis at 7.5 arc-second resolution with 0 meter buffer: `breakline_emphasis_r75_0`).

Usage

```
calc_gmted(
  from,
  locs,
  locs_id = NULL,
  radius = 0,
  fun = "mean",
  geom = FALSE,
  ...
)
```

Arguments

<code>from</code>	SpatRaster(1). Output from <code>process_gmted()</code> .
<code>locs</code>	data.frame. character to file path, SpatVector, or sf object.
<code>locs_id</code>	character(1). Column within locations CSV file containing identifier for each unique coordinate location.
<code>radius</code>	integer(1). Circular buffer distance around site locations. (Default = 0).
<code>fun</code>	character(1). Function used to summarize multiple raster cells within sites location buffer (Default = mean).

geom logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.

... Placeholders

Value

a data.frame or SpatVector object

Author(s)

Mitchell Manware

See Also

[process_gmted\(\)](#)

Examples

```
## NOTE: Example is wrapped in \dontrun{} as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_gridmet(
  from = gmted, # derived from process_gmted() example
  locs = loc,
  locs_id = "id",
  radius = 0,
  fun = "mean",
  geom = FALSE
)

## End(Not run)
```

calc_gridmet

Calculate gridMET covariates

Description

Extract gridMET values at point locations. Returns a data.frame object containing locs_id and gridMET variable. gridMET variable column name reflects the gridMET variable and circular buffer radius.

Usage

```
calc_gridmet(
  from,
  locs,
  locs_id = NULL,
  radius = 0,
```

```

    fun = "mean",
    geom = FALSE,
    ...
)

```

Arguments

from	SpatRaster(1). Output from process_gridmet().
locs	data.frame. character to file path, SpatVector, or sf object.
locs_id	character(1). Column within locations CSV file containing identifier for each unique coordinate location.
radius	integer(1). Circular buffer distance around site locations. (Default = 0).
fun	character(1). Function used to summarize multiple raster cells within sites location buffer (Default = mean).
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Placeholders.

Value

a data.frame or SpatVector object

Author(s)

Mitchell Manware

See Also

[process_gridmet\(\)](#)

Examples

```

## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_gridmet(
  from = gridmet, # derived from process_gridmet() example
  locs = loc,
  locs_id = "id",
  radius = 0,
  fun = "mean",
  geom = FALSE
)

## End(Not run)

```

`calc_hms`*Calculate wildfire smoke covariates*

Description

Extract wildfire smoke plume values at point locations. Returns a `data.frame` object containing `locs_id`, `date`, and binary variable for wildfire smoke plume density inherited from `from` (0 = point not covered by wildfire smoke plume; 1 = point covered by wildfire smoke plume).

Usage

```
calc_hms(from, locs, locs_id = NULL, radius = 0, geom = FALSE, ...)
```

Arguments

<code>from</code>	<code>SpatVector(1)</code> . Output of <code>process_hms()</code> .
<code>locs</code>	<code>data.frame</code> , character to file path, <code>SpatVector</code> , or <code>sf</code> object.
<code>locs_id</code>	<code>character(1)</code> . Column within <code>locations</code> CSV file containing identifier for each unique coordinate location.
<code>radius</code>	<code>integer(1)</code> . Circular buffer distance around site locations. (Default = 0).
<code>geom</code>	<code>logical(1)</code> . Should the function return a <code>SpatVector</code> ? Default is <code>FALSE</code> . The coordinate reference system of the <code>SpatVector</code> is that of <code>from</code> .
<code>...</code>	Placeholders.

Value

a `data.frame` or `SpatVector` object

Author(s)

Mitchell Manware

See Also

[process_hms\(\)](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_hms(
  from = hms, # derived from process_hms() example
  locs = loc,
  locs_id = "id",
  radius = 0,
```

```

    geom = FALSE
  )

  ## End(Not run)

```

calc_koppen_geiger *Calculate climate classification covariates*

Description

Extract climate classification values at point locations. Returns a `data.frame` object containing `locs_id` and binary (0 = point not in climate region; 1 = point in climate region) variables for each climate classification region.

Usage

```

calc_koppen_geiger(
  from = NULL,
  locs = NULL,
  locs_id = "site_id",
  geom = FALSE,
  ...
)

```

Arguments

<code>from</code>	<code>SpatVector(1)</code> . Output of <code>process_koppen_geiger()</code> .
<code>locs</code>	<code>sf/SpatVector</code> . Unique locs. Should include a unique identifier field named <code>locs_id</code>
<code>locs_id</code>	<code>character(1)</code> . Name of unique identifier.
<code>geom</code>	<code>logical(1)</code> . Should the function return a <code>SpatVector</code> ? Default is <code>FALSE</code> . The coordinate reference system of the <code>SpatVector</code> is that of <code>from</code> .
<code>...</code>	Placeholders.

Value

a `data.frame` or `SpatVector` object

Note

The returned object contains a `$description` column to represent the temporal range covered by the dataset. For more information, see <https://www.nature.com/articles/sdata2018214>.

Author(s)

Insang Song

See Also

[process_koppen_geiger](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_koppen_geiger(
  from = kg, # derived from process_koppen_geiger() example
  locs = loc,
  locs_id = "id",
  geom = FALSE
)

## End(Not run)
```

calc_lagged

Calculate temporally lagged covariates

Description

The `calc_lagged()` function calculates daily temporal lagged covariates from the output of `calculate_covariates()` or `calc_*`.

Usage

```
calc_lagged(from, date, lag, locs_id, time_id = "time", geom = FALSE)
```

Arguments

<code>from</code>	<code>data.frame(1)</code> . A <code>data.frame</code> containing calculated covariates returned from <code>calculate_covariates()</code> or <code>calc_*</code> .
<code>date</code>	<code>character(2)</code> . Start and end dates of desired lagged covariates. Length of 10 each, format YYYY-MM-DD (ex. September 1, 2023 = "2023-09-01").
<code>lag</code>	<code>integer(1)</code> . Number of lag days.
<code>locs_id</code>	<code>character(1)</code> . Name of unique identifier.
<code>time_id</code>	<code>character(1)</code> . Column containing time values.
<code>geom</code>	<code>logical(1)</code> . Should the function return a <code>SpatVector</code> ? Default is <code>FALSE</code> . The coordinate reference system of the <code>SpatVector</code> is that of <code>from</code> . To return as a <code>SpatVector</code> , <code>from</code> must also be a <code>SpatVector</code> .

Value

a `data.frame` object

Note

In order to calculate temporally lagged covariates, `from` must contain at least the number of lag days before the desired start date. For example, if `date = c("2024-01-01", "2024-01-31")` and `lag = 1`, `from` must contain data starting at 2023-12-31. If `from` contains geometry features, `calc_lagged` will return a column with geometry features of the same name. `calc_lagged()` assumes that all columns other than `time_id`, `locs_id`, and fixed columns of "lat" and "lon", follow the genre, variable, lag, buffer radius format adopted in `calc_setcolumns()`.

See Also

[calc_covariates\(\)](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
terracliamte_covar <- calc_terraclimate(
  from = terraclimate, # derived from process_terraclimate() example
  locs = loc,
  locs_id = "id",
  radius = 0,
  fun = "mean",
  geom = FALSE
)
calc_lagged(
  from = terracliamte_covar,
  locs_id = "id",
  date = c("2023-01-02", "2023-01-10"),
  lag = 1,
  time_id = "time"
)

## End(Not run)
```

calc_merra2

Calculate meteorological and atmospheric covariates

Description

Extract meteorological and atmospheric values at point locations. Returns a `data.frame` object containing `locs_id`, `date` and `hour`, vertical pressure level, and meteorological or atmospheric variable. Variable column name reflects variable and circular buffer radius.

Usage

```
calc_merra2(
  from,
  locs,
  locs_id = NULL,
  radius = 0,
  fun = "mean",
  geom = FALSE,
  ...
)
```

Arguments

from	SpatRaster(1). Output of process_merra2().
locs	data.frame, character to file path, SpatVector, or sf object.
locs_id	character(1). Column within locations CSV file containing identifier for each unique coordinate location.
radius	integer(1). Circular buffer distance around site locations. (Default = 0).
fun	character(1). Function used to summarize multiple raster cells within sites location buffer (Default = mean).
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Placeholders

Value

a data.frame or SpatVector object

Author(s)

Mitchell Manware

See Also

[calc_geos\(\)](#), [process_merra2\(\)](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_merra2(
  from = merra2, # derived from process_merra2() example
  locs = loc,
  locs_id = "id",
  radius = 0,
  fun = "mean",
```



```

    geom = FALSE
  )

  ## End(Not run)

```

calc_modis_daily *A single-date MODIS worker for parallelization*

Description

The function operates at MODIS/VIIRS products on a daily basis. Given that the raw hdf files are downloaded from NASA, standard file names include a data retrieval date flag starting with letter "A". Leveraging that piece of information, the function will select files of scope on the date of interest. Please note that this function does not provide a function to filter swaths or tiles, so it is strongly recommended to check and pre-filter the file names at users' discretion.

Usage

```

calc_modis_daily(
  from = NULL,
  locs = NULL,
  locs_id = "site_id",
  radius = 0L,
  date = NULL,
  name_extracted = NULL,
  fun_summary = "mean",
  max_cells = 3e+07,
  geom = FALSE,
  ...
)

```

Arguments

from	SpatRaster. Preprocessed objects.
locs	SpatVector/sf/sftime object. Locations where MODIS values are summarized.
locs_id	character(1). Field name where unique site identifiers are stored. Default is "site_id"
radius	numeric. Radius to generate circular buffers.
date	Date(1). date to query.
name_extracted	character. Names of calculated covariates.
fun_summary	function. Summary function for multilayer rasters. Passed to foo. See exactextractr::exact_extract for details.
max_cells	integer(1). Maximum number of cells to be read at once. Higher values will expedite processing, but will increase memory usage. Maximum possible value is $2^{31} - 1$.

geom logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from. See [exactextractr::exact_extract](#) for details.

... Placeholders.

Value

a data.frame or SpatVector object.

Author(s)

Insang Song

See Also

- Preprocessing: [process_modis_merge\(\)](#), [process_modis_swath\(\)](#), [process_blackmarble\(\)](#)
- Parallelization: [calc_modis_par\(\)](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
locs <- data.frame(lon = -78.8277, lat = 35.95013, id = "001")
calc_modis_daily(
  from = mod06l2_warp, # derved from process_modis() example
  locs = locs,
  locs_id = "id",
  radius = 0,
  date = "2024-01-01",
  name_extracted = "cloud_fraction_0",
  fun_summary = "mean",
  max_cells = 3e7
)

## End(Not run)
```

calc_modis_par

Calculate MODIS product covariates in multiple CPU threads

Description

calc_modis_par essentially runs [calc_modis_daily](#) function in each thread (subprocess). Based on daily resolution, each day's workload will be distributed to each thread. With product argument, the files are processed by a customized function where the unique structure and/or characteristics of the products are considered. nthreads argument should be carefully selected in consideration of the machine's CPU and memory capacities as products have their own memory pressure. locs should be sf object as it is exportable to parallel workers.

Usage

```
calc_modis_par(
  from = NULL,
  locs = NULL,
  locs_id = "site_id",
  radius = c(0L, 1000L, 10000L, 50000L),
  preprocess = process_modis_merge,
  name_covariates = NULL,
  subdataset = NULL,
  fun_summary = "mean",
  nthreads = floor(length(parallely::availableWorkers())/2),
  package_list_add = NULL,
  export_list_add = NULL,
  max_cells = 3e+07,
  geom = FALSE,
  ...
)
```

Arguments

from	character. List of paths to MODIS/VIIRS files.
locs	sf/SpatVector object. Unique locs where covariates will be calculated.
locs_id	character(1). Site identifier. Default is "site_id"
radius	numeric. Radii to calculate covariates. Default is c(0, 1000, 10000, 50000).
preprocess	function. Function to handle HDF files.
name_covariates	character. Name header of covariates. e.g., "MOD_NDVIF_0_". The calculated covariate names will have a form of "{name_covariates}{zero-padded buffer radius in meters}", e.g., 'MOD_NDVIF_0_50000' where 50 km radius circular buffer was used to calculate mean NDVI value.
subdataset	Indices, names, or search patterns for subdatasets. Find detail usage of the argument in notes.
fun_summary	character or function. Function to summarize extracted raster values.
nthreads	integer(1). Number of threads to be used to calculate covariates.
package_list_add	character. A vector with package names to load these in each thread. Note that sf, terra, exactextractr, doParallel, parallely and dplyr are the default packages to be loaded.
export_list_add	character. A vector with object names to export to each thread. It should be minimized to spare memory.
max_cells	integer(1). Maximum number of cells to be read at once. Higher values will expedite processing, but will increase memory usage. Maximum possible value is $2^{31} - 1$. See exactextractr::exact_extract for details.

geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Arguments passed to preprocess.

Value

A data.frame or SpatVector with an attribute:

- `attr(, "dates_dropped")`: Dates with insufficient tiles. Note that the dates mean the dates with insufficient tiles, not the dates without available tiles.

Note

Overall, this function and dependent routines assume that the file system can handle concurrent access to the (network) disk by multiple processes. File system characteristics, package versions, and hardware settings and specification can affect the processing efficiency. `locs` is expected to be convertible to `sf` object. `sf`, `SpatVector`, and other class objects that could be converted to `sf` can be used. Common arguments in `preprocess` functions such as `date` and `path` are automatically detected and passed to the function. Please note that `locs` here and `path` in `preprocess` functions are assumed to have a standard naming convention of raw files from NASA. The argument `subdataset` should be in a proper format depending on `preprocess` function:

- `process_modis_merge()`: Regular expression pattern. e.g., `"^LST_"`
- `process_modis_swath()`: Subdataset names. e.g., `c("Cloud_Fraction_Day", "Cloud_Fraction_Night")`
- `process_blackmarble()`: Subdataset number. e.g., for VNP46A2 product, 3L. Dates with less than 80 percent of the expected number of tiles, which are determined by the mode of the number of tiles, are removed. Users will be informed of the dates with insufficient tiles. The result data.frame will have an attribute with the dates with insufficient tiles.

See Also

See details for setting parallelization:

- [future::plan\(\)](#)
- [future.apply::future_lapply\(\)](#)
- [parallelly::makeClusterPSOCK\(\)](#)
- [parallelly::availableCores\(\)](#)

This function leverages the calculation of single-day MODIS covariates:

- [calc_modis_daily\(\)](#)

Also, for preprocessing, please refer to:

- [process_modis_merge\(\)](#)
- [process_modis_swath\(\)](#)
- [process_blackmarble\(\)](#)

Examples

```
## NOTE: Example is wrapped in \dontrun{} as function requires a large
## amount of data which is not included in the package.
## Not run:
locs <- data.frame(lon = -78.8277, lat = 35.95013, id = "001")
locs <- terra::vect(locs, geom = c("lon", "lat"), crs = "EPSG:4326")
calc_modis_par(
  from =
    list.files("./data", pattern = "VNP46A2.", full.names = TRUE),
  locs = locs,
  locs_id = "site_id",
  radius = c(0L, 1000L),
  preprocess = process_modis_merge,
  name_covariates = "cloud_fraction_0",
  subdataset = "Cloud_Fraction",
  fun_summary = "mean",
  nthreads = 1
)

## End(Not run)
```

calc_narr

*Calculate meteorological covariates***Description**

Extract meteorological values at point locations. Returns a `data.frame` object containing `locs_id`, `date`, vertical pressure level, and meteorological variable. Meteorological variable column name reflects variable and circular buffer radius.

Usage

```
calc_narr(
  from,
  locs,
  locs_id = NULL,
  radius = 0,
  fun = "mean",
  geom = FALSE,
  ...
)
```

Arguments

<code>from</code>	SpatRaster(1). Output of <code>process_narr()</code> .
<code>locs</code>	data.frame, character to file path, SpatVector, or sf object.
<code>locs_id</code>	character(1). Column within locations CSV file containing identifier for each unique coordinate location.

radius	integer(1). Circular buffer distance around site locations. (Default = 0).
fun	character(1). Function used to summarize multiple raster cells within sites location buffer (Default = mean).
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Placeholders

Value

a data.frame or SpatVector object

Author(s)

Mitchell Manware

See Also

[process_narr](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_narr(
  from = narr, # derived from process_narr() example
  locs = loc,
  locs_id = "id",
  radius = 0,
  fun = "mean",
  geom = FALSE
)

## End(Not run)
```

calc_nei

Calculate road emissions covariates

Description

Calculate road emissions covariates

Usage

```
calc_nei(from = NULL, locs = NULL, locs_id = "site_id", geom = FALSE, ...)
```

Arguments

from	SpatVector(1). Output of process_nei().
locs	sf/SpatVector. Locations at NEI values are joined.
locs_id	character(1). Unique site identifier column name. Unused but kept for compatibility.
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Placeholders.

Value

a data.frame or SpatVector object

Author(s)

Insang Song, Ranadeep Daw

See Also

[process_nei](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_nei(
  from = nei, # derived from process_nei example
  locs = loc,
  locs_id = "id"
)

## End(Not run)
```

calc_nlcd

Calculate land cover covariates

Description

Compute ratio of land cover class in circle buffers around points. Returns a data.frame object containing locs_id, longitude, latitude, time (year), and computed ratio for each land cover class.

Usage

```
calc_nlcd(
  from,
  locs,
  locs_id = "site_id",
  mode = c("exact", "terra"),
  radius = 1000,
  max_cells = 5e+07,
  geom = FALSE,
  nthreads = 1L,
  ...
)
```

Arguments

from	SpatRaster(1). Output of process_nlcd().
locs	terra::SpatVector of points geometry
locs_id	character(1). Unique identifier of locations
mode	character(1). One of "exact" (using exactextractr::exact_extract()) or "terra" (using terra::freq()).
radius	numeric (non-negative) giving the radius of buffer around points
max_cells	integer(1). Maximum number of cells to be read at once. Higher values may expedite processing, but will increase memory usage. Maximum possible value is $2^{31} - 1$. Only valid when mode = "exact". See exactextractr::exact_extract for details.
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
nthreads	integer(1). Number of threads to be used
...	Placeholders.

Value

a data.frame or SpatVector object

Note

NLCD is available in U.S. only. Users should be aware of the spatial extent of the data. The results are different depending on mode argument. The "terra" mode is less memory intensive but less accurate because it counts the number of cells intersecting with the buffer. The "exact" may be more accurate but uses more memory as it will account for the partial overlap with the buffer.

See Also

[process_nlcd](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_nlcd(
  from = nlcd, # derived from process_nlcd() example
  locs = loc,
  locs_id = "id",
  mode = "exact",
  geom = FALSE
)

## End(Not run)
```

calc_return_locs	<i>Prepare covariates for return</i>
------------------	--------------------------------------

Description

Check the time column for proper class and, if `geom = TRUE`, transform `data.frame` into a `SpatVector` object.

Usage

```
calc_return_locs(covar, POSIXt = TRUE, geom, crs)
```

Arguments

<code>covar</code>	<code>data.frame(1)</code> . Calculated covariates <code>data.frame</code> .
<code>POSIXt</code>	<code>logical(1)</code> . Should the time values in <code>covar</code> be of class <code>POSIXt</code> ? If <code>FALSE</code> , the time values will be checked for integer class (year and year-month).
<code>geom</code>	<code>logical(1)</code> . Should <code>covar</code> be returned as a <code>data.frame</code> ? Default is <code>FALSE</code> .
<code>crs</code>	<code>terra::crs(1)</code> . Coordinate reference system (inherited from <code>from</code>).

Value

a `data.frame` or `SpatVector` object (depending on `geom` paramter)

Author(s)

Mitchell Manware

calc_sedac_groads	<i>Calculate roads covariates</i>
-------------------	-----------------------------------

Description

Prepared groads data is clipped with the buffer polygons of radius. The total length of the roads are calculated. Then the density of the roads is calculated by dividing the total length from the area of the buffer. `terra::linearUnits()` is used to convert the unit of length to meters.

Usage

```
calc_sedac_groads(
  from = NULL,
  locs = NULL,
  locs_id = NULL,
  radius = 1000,
  fun = "sum",
  geom = FALSE,
  ...
)
```

Arguments

<code>from</code>	<code>SpatVector(1)</code> . Output of <code>process_sedac_groads</code> .
<code>locs</code>	<code>data.frame</code> , character to file path, <code>SpatVector</code> , or <code>sf</code> object.
<code>locs_id</code>	<code>character(1)</code> . Column within <code>locations</code> CSV file containing identifier for each unique coordinate location.
<code>radius</code>	<code>integer(1)</code> . Circular buffer distance around site locations. (Default = 1000).
<code>fun</code>	<code>function(1)</code> . Function used to summarize the length of roads within sites location buffer (Default is <code>sum</code>).
<code>geom</code>	<code>logical(1)</code> . Should the function return a <code>SpatVector</code> ? Default is <code>FALSE</code> . The coordinate reference system of the <code>SpatVector</code> is that of <code>from</code> .
<code>...</code>	Placeholders.

Value

a `data.frame` or `SpatVector` object

Note

Unit is km / sq km. The returned `data.frame` object contains a `$time` column to represent the temporal range covered by the dataset. For more information, see <https://sedac.ciesin.columbia.edu/data/set/groads-global-roads-open-access-v1/metadata>.

Author(s)

Insang Song

See Also[process_sedac_groads](#)**Examples**

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_sedac_groads(
  from = groads, # derived from process_sedac_groads() example
  locs = loc,
  locs_id = "id",
  radius = 1000,
  fun = "sum",
  geom = FALSE
)

## End(Not run)
```

calc_sedac_population *Calculate population density covariates*

Description

Extract population density values at point locations. Returns a data.frame object containing locs_id, year, and population density variable. Population density variable column name reflects spatial resolution of from and circular buffer radius.

Usage

```
calc_sedac_population(
  from,
  locs,
  locs_id = NULL,
  radius = 0,
  fun = "mean",
  geom = FALSE,
  ...
)
```

Arguments

from	SpatRaster(1). Output of process_sedac_population().
locs	data.frame, character to file path, SpatVector, or sf object.
locs_id	character(1). Column within locations CSV file containing identifier for each unique coordinate location.

radius	integer(1). Circular buffer distance around site locations. (Default = 0).
fun	character(1). Function used to summarize multiple raster cells within sites location buffer (Default = mean).
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Placeholders

Value

a data.frame or SpatVector object

Author(s)

Mitchell Manware

See Also

[process_sedac_population\(\)](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_sedac_population(
  from = pop, # derived from process_sedac_population() example
  locs = loc,
  locs_id = "id",
  radius = 0,
  fun = "mean",
  geom = FALSE
)

## End(Not run)
```

calc_sedc

Calculate Sum of Exponentially Decaying Contributions (SEDC) covariates

Description

Calculate Sum of Exponentially Decaying Contributions (SEDC) covariates

Usage

```
calc_sedc(
  from = NULL,
  locs = NULL,
  locs_id = NULL,
  sedc_bandwidth = NULL,
  target_fields = NULL,
  geom = FALSE
)
```

Arguments

from	SpatVector object. Locations where each SEDC is calculated.
locs	SpatVector object. Locations where the sum of SEDCs are calculated.
locs_id	character(1). Name of the unique id field in point_to.
sedc_bandwidth	numeric(1). Distance at which the source concentration is reduced to $\exp(-3)$ (approximately -95 %)
target_fields	character(varying). Field names in characters.
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.

Value

a data.frame (tibble) or SpatVector object with input field names with a suffix "_sedc" where the sums of EDC are stored. Additional attributes are attached for the EDC information.

- 'attr(result, "sedc_bandwidth")': the bandwidth where concentration reduces to approximately five percent
- 'attr(result, "sedc_threshold")': the threshold distance at which emission source points are excluded beyond that

Note

The function is originally from [chopin](#). Distance calculation is done with terra functions internally. Thus, the function internally converts sf objects in point_* arguments to terra. The threshold should be carefully chosen by users.

Author(s)

Insang Song

References

Messier KP, Akita Y, Serre ML (2012). "Integrating Address Geocoding, Land Use Regression, and Spatiotemporal Geostatistical Estimation for Groundwater Tetrachloroethylene." *Environmental Science & Technology*, **46**(5), 2772–2780. ISSN 0013-936X, doi:10.1021/es203152a.

Wiesner C (????). "Euclidean Sum of Exponentially Decaying Contributions Tutorial."

Examples

```

library(terra)
library(sf)
set.seed(101)
ncpath <- system.file("gpkg/nc.gpkg", package = "sf")
nc <- terra::vect(ncpath)
nc <- terra::project(nc, "EPSG:5070")
pnt_locs <- terra::centroids(nc, inside = TRUE)
pnt_locs <- pnt_locs[, "NAME"]
pnt_from <- terra::spatSample(nc, 10L)
pnt_from$pid <- seq(1, 10)
pnt_from <- pnt_from[, "pid"]
pnt_from$val1 <- rgamma(10L, 1, 0.05)
pnt_from$val2 <- rgamma(10L, 2, 1)

vals <- c("val1", "val2")
calc_sedc(pnt_locs, pnt_from, "NAME", 1e4, vals)

```

calc_temporal_dummies *Calculate temporal dummy covariates*

Description

Calculate temporal dummy covariates at point locations. Returns a data.frame object with locs_id, year binary variable for each value in year, and month and day of week binary variables.

Usage

```

calc_temporal_dummies(
  locs,
  locs_id = "site_id",
  year = seq(2018L, 2022L),
  geom = FALSE,
  ...
)

```

Arguments

locs	data.frame with a temporal field named "time"
locs_id	character(1). Unique site identifier column name. Default is "site_id".
year	integer. Year domain to dummify. Default is seq(2018L, 2022L).
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Placeholders.

Value

a data.frame or SpatVector object

Author(s)

Insang Song

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_temporal_dummies(
  locs = loc,
  locs_id = "id",
  year = seq(2018L, 2022L)
)

## End(Not run)
```

calc_terraclimate	<i>Calculate TerraClimate covariates</i>
-------------------	--

Description

Extract TerraClimate values at point locations. Returns a data.frame object containing locs_id and TerraClimate variable. TerraClimate variable column name reflects the TerraClimate variable and circular buffer radius.

Usage

```
calc_terraclimate(
  from = NULL,
  locs = NULL,
  locs_id = NULL,
  radius = 0,
  fun = "mean",
  geom = FALSE,
  ...
)
```

Arguments

from	SpatRaster(1). Output from process_terraclimate().
locs	data.frame. character to file path, SpatVector, or sf object.
locs_id	character(1). Column within locations CSV file containing identifier for each unique coordinate location.
radius	integer(1). Circular buffer distance around site locations. (Default = 0).
fun	character(1). Function used to summarize multiple raster cells within sites location buffer (Default = mean).

geom logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.

... Placeholders.

Value

a data.frame or SpatVector object

Note

TerraClimate data has monthly temporal resolution, so the \$time column will contain the year and month in YYYYMM format (ie. January, 2018 = 201801).

Author(s)

Mitchell Manware

See Also

[process_terraclimate\(\)](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_terraclimate(
  from = terraclimate, # derived from process_terraclimate() example
  locs = loc,
  locs_id = "id",
  radius = 0,
  fun = "mean",
  geom = FALSE
)

## End(Not run)
```

calc_tri

Calculate toxic release covariates

Description

Extract toxic release values at point locations. Returns a data.frame object containing locs_id and variables for each chemical in from.

Usage

```
calc_tri(
  from = NULL,
  locs,
  locs_id = "site_id",
  radius = c(1000L, 10000L, 50000L),
  geom = FALSE,
  ...
)
```

Arguments

from	SpatVector(1). Output of process_tri().
locs	sf/SpatVector. Locations where TRI variables are calculated.
locs_id	character(1). Unique site identifier column name. Default is "site_id".
radius	Circular buffer radius. Default is c(1000, 10000, 50000) (meters)
geom	logical(1). Should the function return a SpatVector? Default is FALSE. The coordinate reference system of the SpatVector is that of from.
...	Placeholders.

Value

a data.frame or SpatVector object

Note

U.S. context.

Author(s)

Insang Song, Mariana Kassien

See Also

[calc_sedc](#), [process_tri](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
loc <- data.frame(id = "001", lon = -78.90, lat = 35.97)
calc_tri(
  from = tri, # derived from process_tri() example
  locs = loc,
  locs_id = "id",
  radius = c(1e3L, 1e4L, 5e4L)
)
```

```
## End(Not run)
```

check_mysf	<i>Check sf object</i>
------------	------------------------

Description

Check an sf object for its class, \$geometry column, and geometry class.

Usage

```
check_mysf(x)
```

Arguments

x an sf object

Value

NULL; returns stop error if x does not match class and/or column expectations

Author(s)

Eva Marques

check_mysftime	<i>Check sftime object</i>
----------------	----------------------------

Description

Check an sftime object for its class, \$time column, \$geometry column, and geometry class.

Usage

```
check_mysftime(x)
```

Arguments

x an sftime object

Value

NULL; returns stop error if x does not match class and column expectations

Author(s)

Eva Marques

check_urls	<i>Implement check_url_status</i>
------------	-----------------------------------

Description

Apply `check_url_status()` function to a sample of download URLs.

Usage

```
check_urls(urls = urls, size = NULL, method = c("HEAD", "GET", "SKIP"))
```

Arguments

urls	character vector of URLs
size	number of observations to be sampled from <code>urls</code>
method	htrr method to obtain URL ("HEAD" or "GET"). If set to "SKIP", the HTTP status will not be checked and returned.

Value

logical vector for URL status = 200

check_url_status	<i>Check HTTP status</i>
------------------	--------------------------

Description

Check if provided URL returns HTTP status 200 or 206.

Usage

```
check_url_status(url, method = c("HEAD", "GET"))
```

Arguments

url	Download URL to be checked.
method	htrr method to obtain URL ("HEAD" or "GET")

Value

logical object

Author(s)

Insang Song; Mitchell Manware

download_aqs	<i>Download air quality data</i>
--------------	----------------------------------

Description

The `download_aqs()` function accesses and downloads Air Quality System (AQS) data from the [U.S. Environmental Protection Agency's \(EPA\) Pre-Generated Data Files](#).

Usage

```
download_aqs(
  parameter_code = 88101,
  resolution_temporal = "daily",
  year = c(2018, 2022),
  url_aqs_download = "https://aqs.epa.gov/aqsweb/airdata/",
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE,
  unzip = TRUE,
  remove_zip = FALSE
)
```

Arguments

<code>parameter_code</code>	integer(1). length of 5. EPA pollutant parameter code. For details, please refer to AQS parameter codes
<code>resolution_temporal</code>	character(1). Name of column containing POC values. Currently, no value other than "daily" works.
<code>year</code>	character(2). length of 4 each. Start/end years for downloading data.
<code>url_aqs_download</code>	character(1). URL to the AQS pre-generated datasets.
<code>directory_to_save</code>	character(1). Directory to save data. Two sub-directories will be created for the downloaded zip files (" <code>zip_files</code> ") and the unzipped data files (" <code>data_files</code> ").
<code>acknowledgement</code>	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
<code>download</code>	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
<code>remove_command</code>	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands. Default is FALSE.
<code>unzip</code>	logical(1). Unzip zip files. Default TRUE.
<code>remove_zip</code>	logical(1). Remove zip file from <code>directory_to_download</code> . Default FALSE.

Value

NULL; Zip and/or data files will be downloaded and stored in `directory_to_save`.

Author(s)

Mariana Kassien, Insang Song, Mitchell Manware

References

U.S. Environmental Protection Agency (2023). "Air Quality System Data Mart [internet database]."
<https://www.epa.gov/outdoor-air-quality-data>.

Examples

```
download_aqs(  
  parameter_code = 88101,  
  resolution_temporal = "daily",  
  year = c(2023, 2023),  
  directory_to_save = tempdir(),  
  acknowledgement = TRUE,  
  download = FALSE, # NOTE: download skipped for examples,  
  remove_command = TRUE,  
  unzip = FALSE  
)
```

download_cropscape *Download CropScape data*

Description

Accesses and downloads United States Department of Agriculture CropScape Cropland Data Layer data from the [USDA National Agricultural Statistics Service](#) or the [George Mason University website](#).

Usage

```
download_cropscape(  
  year = seq(1997, 2023),  
  source = c("USDA", "GMU"),  
  directory_to_save = NULL,  
  acknowledgement = FALSE,  
  download = FALSE,  
  remove_command = FALSE,  
  unzip = TRUE  
)
```

Arguments

year	integer(1). Year of the data to download.
source	character(1). Data source, one of c("USDA", "GMU"). <ul style="list-style-type: none">• "USDA" will download the national data from the USDA website (available in 2008-last year).• "GMU" will download the data from the George Mason University website (available in 1997-last year).
directory_to_save	character(1). Directory to download files.
acknowledgement	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
download	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
remove_command	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.
unzip	logical(1). Unzip the downloaded compressed files. Default is FALSE.

Value

NULL; Yearly comma-separated value (CSV) files will be stored in `directory_to_save`.

Note

JSON files should be found at STAC catalog of OpenLandMap

Author(s)

Insang Song

Examples

```
download_cropscape(  
  year = 2020,  
  source = "USDA",  
  directory_to_save = tempdir(),  
  acknowledgement = TRUE,  
  download = FALSE, # NOTE: download skipped for examples,  
  remove_command = TRUE,  
  unzip = FALSE  
)
```

download_data	<i>Download raw data wrapper function</i>
---------------	---

Description

The `download_data()` function accesses and downloads atmospheric, meteorological, and environmental data from various open-access data sources.

Usage

```
download_data(  
  dataset_name = c("aqs", "ecoregion", "ecoregions", "geos", "gmted", "koppen",  
    "koppengeiger", "merra2", "merra", "modis", "narr", "nlcd", "noaa", "sedac_groads",  
    "sedac_population", "groads", "population", "hms", "smoke", "tri", "nei", "gridmet",  
    "terraclimate", "huc", "cropscape", "cdl", "prism"),  
  directory_to_save = NULL,  
  acknowledgement = FALSE,  
  ...  
)
```

Arguments

`dataset_name` character(1). Dataset to download.

`directory_to_save` character(1). Directory to save / unzip (if zip files are downloaded) data.

`acknowledgement` logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.

... Arguments passed to each download function.

Value

NULL; Data files will be downloaded and stored in respective sub-directories within `directory_to_save`. File format and sub-directory names depend on data source and dataset of interest.

Note

- All download function names are in `download_*` formats

Author(s)

Insang Song

See Also

For details of each download function per dataset, Please refer to:

- `download_aqs`: "aqs", "AQS"
- `download_ecoregion`: "ecoregions", "ecoregion"
- `download_geos`: "geos"
- `download_gmted`: "gmted", "GMTED"
- `download_koppen_geiger`: "koppen", "koppengeiger"
- `download_merra2`: "merra2", "merra", "MERRA", "MERRA2"
- `download_narr`: "narr"
- `download_nlcd`: "nlcd", "NLCD"
- `download_hms`: "noaa", "smoke", "hms"
- `download_sedac_groads`: "sedac_groads", "groads"
- `download_sedac_population`: "sedac_population", "population"
- `download_modis`: "modis", "MODIS"
- `download_tri`: "tri", "TRI"
- `download_nei`: "nei", "NEI"
- `download_gridmet`: "gridMET", "gridmet"
- `download_terraclimate`: "TerraClimate", "terraclimate"
- `download_huc`: "huc"
- `download_cropscape`: "cropscape", "cdl"
- `download_prism`: "prism"

Examples

```
download_data(  
  dataset_name = "narr",  
  variables = "weasd",  
  year = c(2023, 2023),  
  directory_to_save = tempdir(),  
  acknowledgement = TRUE,  
  download = FALSE, # NOTE: download skipped for examples,  
  remove_command = TRUE  
)
```

download_ecoregion *Download ecoregion data*

Description

The `download_ecoregion()` function accesses and downloads United States Ecoregions data from the [U.S. Environmental Protection Agency's \(EPA\) Ecoregions](#). Level 3 data, where all pieces of information in the higher levels are included, are downloaded.

Usage

```
download_ecoregion(
  epa_certificate_path = system.file("extdata/cacert_gaftp_epa.pem", package = "amadeus"),
  certificate_url =
    "http://cacerts.digicert.com/DigiCertGlobalG2TLRSASHA2562020CA1-1.crt",
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE,
  unzip = TRUE,
  remove_zip = FALSE
)
```

Arguments

<code>epa_certificate_path</code>	character(1). Path to the certificate file for EPA DataCommons. Default is 'ext-data/cacert_gaftp_epa.pem' under the package installation path.
<code>certificate_url</code>	character(1). URL to certificate file. See notes for details.
<code>directory_to_save</code>	character(1). Directory to save data. Two sub-directories will be created for the downloaded zip files ("/zip_files") and the unzipped data files ("/data_files").
<code>acknowledgement</code>	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
<code>download</code>	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
<code>remove_command</code>	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.
<code>unzip</code>	logical(1). Unzip zip files. Default TRUE.
<code>remove_zip</code>	logical(1). Remove zip file from directory_to_download. Default FALSE.

Value

NULL; Zip and/or data files will be downloaded and stored in `directory_to_save`.

Note

For EPA Data Commons certificate errors, follow the steps below:

1. Click Lock icon in the address bar at <https://gaftp.epa.gov>
2. Click Show Certificate
3. Access Details
4. Find URL with *.crt extension Currently we bundle the pre-downloaded crt and its PEM (which is accepted in wget command) file in `./inst/extdata`. The instruction above is for certificate updates in the future.

Author(s)

Insang Song

References

Omernik JM, Griffith GE (2014). “Ecoregions of the Conterminous United States: Evolution of a Hierarchical Spatial Framework.” *Environmental Management*, **54**(6), 1249–1266. ISSN 0364-152X, 1432-1009, doi:[10.1007/s0026701403641](https://doi.org/10.1007/s0026701403641), <https://link.springer.com/article/10.1007/s00267-014-0364-1>.

Examples

```
download_ecoregion(
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE,
  unzip = FALSE
)
```

download_geos

Download atmospheric composition data

Description

The `download_geos()` function accesses and downloads various atmospheric composition collections from [NASA’s Global Earth Observing System \(GEOS\) model](#).

Usage

```
download_geos(
  collection = c("aqc_tavg_1hr_g1440x721_v1", "chm_tavg_1hr_g1440x721_v1",
    "met_tavg_1hr_g1440x721_x1", "xgc_tavg_1hr_g1440x721_x1",
    "chm_inst_1hr_g1440x721_p23", "met_inst_1hr_g1440x721_p23"),
  date = c("2018-01-01", "2018-01-01"),
  directory_to_save = NULL,
```

```

    acknowledgement = FALSE,
    download = FALSE,
    remove_command = FALSE
  )

```

Arguments

collection character(1). GEOS-CF data collection file name.

date character(2). length of 10 each. Start/end date for downloading data. Format "YYYY-MM-DD" (ex. January 1, 2018 = "2018-01-01").

directory_to_save character(1). Directory to save data. Sub-directories will be created within `directory_to_save` for each GEOS-CF collection.

acknowledgement logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.

download logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.

remove_command logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

Value

NULL; netCDF (.nc4) files will be stored in a collection-specific folder within `directory_to_save`.

Author(s)

Mitchell Manware, Insang Song

References

Keller CA, Knowland KE, Duncan BN, Liu J, Anderson DC, Das S, Lucchesi RA, Lundgren EW, Nicely JM, Nielsen E, Ott LE, Saunders E, Strode SA, Wales PA, Jacob DJ, Pawson S (2021). "Description of the NASA GEOS Composition Forecast Modeling System GEOS-CF v1.0." *Journal of Advances in Modeling Earth Systems*, **13**(4), e2020MS002413. ISSN 1942-2466, 1942-2466, [doi:10.1029/2020MS002413](https://doi.org/10.1029/2020MS002413).

Examples

```

download_geos(
  collection = "aqc_tavg_1hr_g1440x721_v1",
  date = c("2024-01-01", "2024-01-01"),
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE
)

```

download_gmted	<i>Download elevation data</i>
----------------	--------------------------------

Description

The `download_gmted()` function accesses and downloads Global Multi-resolution Terrain Elevation Data (GMTED2010) from [U.S. Geological Survey and National Geospatial-Intelligence Agency](#).

Usage

```
download_gmted(
  statistic = c("Breakline Emphasis", "Systematic Subsample", "Median Statistic",
    "Minimum Statistic", "Mean Statistic", "Maximum Statistic",
    "Standard Deviation Statistic"),
  resolution = c("7.5 arc-seconds", "15 arc-seconds", "30 arc-seconds"),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE,
  unzip = TRUE,
  remove_zip = FALSE
)
```

Arguments

<code>statistic</code>	character(1). Available statistics include "Breakline Emphasis", "Systematic Subsample", "Median Statistic", "Minimum Statistic", "Mean Statistic", "Maximum Statistic", and "Standard Deviation Statistic".
<code>resolution</code>	character(1). Available resolutions include "7.5 arc-seconds", "15 arc-seconds", and "30 arc-seconds".
<code>directory_to_save</code>	character(1). Directory to save data. Two sub-directories will be created for the downloaded zip files ("/zip_files") and the unzipped data files ("/data_files").
<code>acknowledgement</code>	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
<code>download</code>	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
<code>remove_command</code>	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands. Default is FALSE.
<code>unzip</code>	logical(1). Unzip zip files. Default is TRUE.
<code>remove_zip</code>	logical(1). Remove zip file from directory_to_download. Default is FALSE.

Value

NULL; Zip and/or data files will be downloaded and stored in `directory_to_save`.

Author(s)

Mitchell Manware, Insang Song

References

Danielson JJ, Gesch DB (2011). "Global multi-resolution terrain elevation data 2010 (GMTED2010)," Open-File Report 2011-1073, U.S. Geological Survey. Series: Open-File Report, <https://doi.org/10.3133/ofr20111073>.

Examples

```
download_gmted(  
  statistic = "Breakline Emphasis",  
  resolution = "7.5 arc-seconds",  
  directory_to_save = tempdir(),  
  acknowledgement = TRUE,  
  download = FALSE, # NOTE: download skipped for examples,  
  remove_command = TRUE,  
  unzip = FALSE  
)
```

download_gridmet *Download gridMET data*

Description

The `download_gridmet` function accesses and downloads gridded surface meteorological data from the [University of California Merced Climatology Lab's gridMET dataset](#).

Usage

```
download_gridmet(  
  variables = NULL,  
  year = c(2018, 2022),  
  directory_to_save = NULL,  
  acknowledgement = FALSE,  
  download = FALSE,  
  remove_command = FALSE  
)
```

Arguments

variables	character(1). Variable(s) name(s). See gridMET Generate Wget File for variable names and acronym codes. (Note: variable "Burning Index" has code "bi" and variable "Energy Release Component" has code "erc").
year	character(2). length of 4 each. Start/end years for downloading data.
directory_to_save	character(1). Directory(s) to save downloaded data files.
acknowledgement	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
download	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
remove_command	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

Value

NULL; netCDF (.nc) files will be stored in a variable-specific folder within `directory_to_save`.

Author(s)

Mitchell Manware

References

Abatzoglou JT (2013). "Development of gridded surface meteorological data for ecological applications and modelling." *International journal of climatology*, **33**(1), 121–131.

Examples

```
download_gridmet(
  variables = "Precipitation",
  year = c(2023, 2023),
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE
)
```

download_hms

Download wildfire smoke data

Description

The `download_hms()` function accesses and downloads wildfire smoke plume coverage data from [NOAA's Hazard Mapping System Fire and Smoke Product](#).

Usage

```
download_hms(
  data_format = "Shapefile",
  date = c("2018-01-01", "2018-01-01"),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE,
  unzip = TRUE,
  remove_zip = FALSE
)
```

Arguments

data_format character(1). "Shapefile" or "KML".

date character(2). length of 10 each. Start/end date for downloading data.

directory_to_save character(1). Directory to save data. If `data_format = "Shapefile"`, two sub-directories will be created for the downloaded zip files ("`zip_files`") and the unzipped shapefiles ("`data_files`"). If `data_format = "KML"`, a single sub-directory ("`data_files`") will be created.

acknowledgement logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.

download logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.

remove_command logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

unzip logical(1). Unzip zip files. Default is TRUE. (Ignored if `data_format = "KML"`.)

remove_zip logical(1). Remove zip files from `directory_to_download`. Default is FALSE. (Ignored if `data_format = "KML"`.)

Value

NULL; Zip and/or data files will be downloaded and stored in respective sub-directories within `directory_to_save`.

Author(s)

Mitchell Manware, Insang Song

References

(???). "Hazard Mapping System Fire and Smoke Product: Hazard Mapping System." <https://www.ospo.noaa.gov/products/land/hms.html#about>. <https://www.ospo.noaa.gov/products/land/hms.html#about>.

Examples

```
download_hms(
  data_format = "Shapefile",
  date = c("2024-01-01", "2024-01-01"),
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE,
  unzip = FALSE
)
```

download_huc

Download National Hydrography Dataset (NHD) data

Description

NHDPlus data provides the most comprehensive and high-resolution hydrography data. This function downloads **national** dataset from NHDPlus Version 2.1 on USGS Amazon S3 storage.

Usage

```
download_huc(
  region = c("Lower48", "Islands"),
  type = c("Seamless", "OceanCatchment"),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE,
  unzip = FALSE
)
```

Arguments

region	character(1). One of c("Lower48", "Islands"). When "Islands" is selected, the data will be downloaded for Hawaii, Puerto Rico, and Virgin Islands.
type	character(1). One of c("Seamless", "OceanCatchment").
directory_to_save	character(1). Directory to download files.
acknowledgement	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
download	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
remove_command	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.
unzip	logical(1). Unzip the downloaded compressed files. Default is FALSE. Not working for this function since HUC data is in 7z format.

Value

NULL; Downloaded files will be stored in `directory_to_save`.

Note

For HUC, set `type = "Seamless"`. HUC12 layer presents in the seamless geodatabase. Users can aggregate HUC12 layer to make HUC6, HUC8, HUC10, etc. For whom wants to download a specific region, please visit [Get NHDPlus Data](#)

Author(s)

Insang Song

References

U.S. Geological Survey (2023). "National Hydrography Dataset (NHD) – USGS National Map Downloadable Data Collection." <https://www.usgs.gov/national-hydrography>.

Examples

```
download_huc(  
  region = "Lower48",  
  type = "Seamless",  
  directory_to_save = tempdir(),  
  acknowledgement = TRUE,  
  download = FALSE, # NOTE: download skipped for examples,  
  remove_command = TRUE,  
  unzip = FALSE  
)
```

download_koppen_geiger

Download climate classification data

Description

The `download_koppen_geiger()` function accesses and downloads climate classification data from the *Present and future Köppen-Geiger climate classification maps at 1-km resolution* ([link for article](#); [link for data](#)).

Usage

```
download_koppen_geiger(  
  data_resolution = c("0.0083", "0.083", "0.5"),  
  time_period = c("Present", "Future"),  
  directory_to_save = NULL,  
  acknowledgement = FALSE,  
  download = FALSE,
```

```

remove_command = FALSE,
unzip = TRUE,
remove_zip = FALSE
)

```

Arguments

`data_resolution` character(1). Available resolutions are "0.0083" degrees (approx. 1 km), "0.083" degrees (approx. 10 km), and "0.5" degrees (approx. 50 km).

`time_period` character(1). Available times are "Present" (1980-2016) and "Future" (2071-2100). ("Future" classifications are based on scenario RCP8.5).

`directory_to_save` character(1). Directory to save data. Two sub-directories will be created for the downloaded zip files ("/zip_files") and the unzipped shapefiles ("/data_files").

`acknowledgement` logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.

`download` logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.

`remove_command` logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

`unzip` logical(1). Unzip zip files. Default is TRUE.

`remove_zip` logical(1). Remove zip files from directory_to_download. Default is FALSE.

Value

NULL; Zip and/or data files will be downloaded and stored in respective sub-directories within `directory_to_save`.

Author(s)

Mitchell Manware, Insang Song

References

Beck HE, McVicar TR, Vergopolan N, Berg A, Lutsko NJ, Dufour A, Zeng Z, Jiang X, Van Dijk AIJM, Miralles DG (2023). "High-resolution (1 km) Köppen-Geiger maps for 1901–2099 based on constrained CMIP6 projections." *Scientific Data*, **10**(1), 724. ISSN 2052-4463, doi:10.1038/s41597023025496, <https://www.nature.com/articles/s41597-023-02549-6>.

Beck HE, Zimmermann NE, McVicar TR, Vergopolan N, Berg A, Wood EF (2018). "Present and future Köppen-Geiger climate classification maps at 1-km resolution." *Scientific data*, **5**(1), 1–12. doi:10.1038/sdata.2018.214.

Examples

```
download_koppen_geiger(
  data_resolution = "0.0083",
  time_period = "Present",
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE,
  unzip = FALSE
)
```

download_merra2	<i>Download meteorological and atmospheric data</i>
-----------------	---

Description

The `download_merra2()` function accesses and downloads various meteorological and atmospheric collections from [NASA's Modern-Era Retrospective analysis for Research and Applications, Version 2 \(MERRA-2\) model](#).

Usage

```
download_merra2(
  collection = c("inst1_2d_asm_Nx", "inst1_2d_int_Nx", "inst1_2d_lfo_Nx",
    "inst3_3d_asm_Np", "inst3_3d_aer_Nv", "inst3_3d_asm_Nv", "inst3_3d_chm_Nv",
    "inst3_3d_gas_Nv", "inst3_2d_gas_Nx", "inst6_3d_ana_Np", "inst6_3d_ana_Nv",
    "statD_2d_slv_Nx", "tavg1_2d_adg_Nx", "tavg1_2d_aer_Nx", "tavg1_2d_chm_Nx",
    "tavg1_2d_csp_Nx", "tavg1_2d_flx_Nx", "tavg1_2d_int_Nx", "tavg1_2d_lfo_Nx",
    "tavg1_2d_lnd_Nx", "tavg1_2d_ocn_Nx", "tavg1_2d_rad_Nx", "tavg1_2d_slv_Nx",
    "tavg3_3d_mst_Ne", "tavg3_3d_trb_Ne", "tavg3_3d_nav_Ne", "tavg3_3d_cld_Np",

    "tavg3_3d_mst_Np", "tavg3_3d_rad_Np", "tavg3_3d_tdt_Np", "tavg3_3d_trb_Np",
    "tavg3_3d_udt_Np", "tavg3_3d_odt_Np", "tavg3_3d_qdt_Np", "tavg3_3d_asm_Nv",
    "tavg3_3d_cld_Nv", "tavg3_3d_mst_Nv", "tavg3_3d_rad_Nv", "tavg3_2d_glc_Nx"),
  date = c("2018-01-01", "2018-01-01"),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE
)
```

Arguments

collection	character(1). MERRA-2 data collection file name.
date	character(2). length of 10 each. Start/end date for downloading data. Format "YYYY-MM-DD" (ex. January 1, 2018 = "2018-01-01").

directory_to_save	character(1). Directory to save data.
acknowledgement	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
download	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
remove_command	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

Value

NULL; netCDF (.nc4) files will be stored in a collection-specific folder within `directory_to_save`.

Author(s)

Mitchell Manware, Insang Song

References

- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 inst1_2d_asm_Nx: 2d,3-Hourly,Instantaneous,Single-Level,Assimilation,Single-Level Diagnostics V5.12.4." doi:10.5067/3Z173KIE2TPD, https://disc.gsfc.nasa.gov/datasets/M2I1NXASM_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 inst1_2d_int_Nx: 2d,1-Hourly,Instantaneous,Single-Level,Assimilation,Vertically Integrated Diagnostics V5.12.4." doi:10.5067/G0U6NGQ3BLE0, https://disc.gsfc.nasa.gov/datasets/M2I1NXINT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 inst1_2d_lfo_Nx: 2d,1-Hourly,Instantaneous,Single-Level,Assimilation,Land Surface Forcings V5.12.4." doi:10.5067/RCMZA6TL70BG, https://disc.gsfc.nasa.gov/datasets/M2I1NXLF0_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 inst3_3d_asm_Np: 3d,3-Hourly,Instantaneous,Pressure-Level,Assimilation,Assimilated Meteorological Fields V5.12.4." doi:10.5067/QBZ6MG944HW0, https://disc.gsfc.nasa.gov/datasets/M2I3NPASM_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 inst3_3d_aer_Nv: 3d,3-Hourly,Instantaneous,Model-Level,Assimilation,Aerosol Mixing Ratio V5.12.4." doi:10.5067/LTVB4GPCOTK2, https://disc.gsfc.nasa.gov/datasets/M2I3NVAER_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 inst3_3d_asm_Nv: 3d,3-Hourly,Instantaneous,Model-Level,Assimilation,Assimilated Meteorological Fields V5.12.4." doi:10.5067/WWQSQ8IVFW8, https://disc.gsfc.nasa.gov/datasets/M2I3NVASM_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 inst3_3d_chm_Nv: 3d,3-Hourly,Instantaneous,Model-Level,Assimilation,Carbon Monoxide and Ozone Mixing Ratio V5.12.4." doi:10.5067/HO9OVZWF3KW2, https://disc.gsfc.nasa.gov/datasets/M2I3NVCHM_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 inst3_3d_gas_Nv: 3d,3-Hourly,Instantaneous,Model-Level,Assimilation,Aerosol Mixing Ratio Analysis Increments

V5.12.4.” doi:10.5067/96BUID8HGGX5, https://disc.gsfc.nasa.gov/datasets/M2I3NVGAS_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 inst3_2d_gas_Nx: 2d,3-Hourly,Instantaneous,Single-Level,Assimilation,Aerosol Optical Depth Analysis V5.12.4.” doi:10.5067/HNGA0EWW0R09, https://disc.gsfc.nasa.gov/datasets/M2I3NXGAS_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 inst6_3d_ana_Np: 3d,6-Hourly,Instantaneous,Pressure-Level,Analysis,Analyzed Meteorological Fields V5.12.4.” doi:10.5067/A7S6XP56VZWS, https://disc.gsfc.nasa.gov/datasets/M2I6NPANA_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 inst6_3d_ana_Nv: 3d,6-Hourly,Instantaneous,Model-Level,Analysis,Analyzed Meteorological Fields V5.12.4.” doi:10.5067/IUUF4WB9FT4W, https://disc.gsfc.nasa.gov/datasets/M2I6NVANA_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 statD_2d_slv_Nx: 2d,Monthly,Aggregated Statistics,Single-Level,Assimilation,Single-Level Diagnostics V5.12.4.” doi:10.5067/KVIMOMCUO83U, https://disc.gsfc.nasa.gov/datasets/M2SMNXSLV_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 statD_2d_slv_Nx: 2d,Daily,Aggregated Statistics,Single-Level,Assimilation,Single-Level Diagnostics V5.12.4.” doi:10.5067/9SC1VNTWGWV3, https://disc.gsfc.nasa.gov/datasets/M2SDNXSLV_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_adg_Nx: 2d,3-Hourly,Time-averaged,Single-Level,Assimilation,Aerosol Diagnostics (extended) V5.12.4.” doi:10.5067/HM00OHQBHKTP, https://disc.gsfc.nasa.gov/datasets/M2T1NXADG_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_aer_Nx: 2d,1-Hourly,Time-averaged,Single-Level,Assimilation,Aerosol Diagnostics V5.12.4.” doi:10.5067/KLICLTZ8EM9D, https://disc.gsfc.nasa.gov/datasets/M2T1NXAER_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_chm_Nx: 2d,3-Hourly,Time-Averaged,Single-Level,Assimilation,Carbon Monoxide and Ozone Diagnostics V5.12.4.” doi:10.5067/3RQ5YS674DGQ, https://disc.gsfc.nasa.gov/datasets/M2T1NXCHM_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_csp_Nx: 2d,1-Hourly,Time-averaged,Single-Level,Assimilation,COSP Satellite Simulator V5.12.4.” doi:10.5067/H0VVAD8F6MX5, https://disc.gsfc.nasa.gov/datasets/M2T1NXCSP_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_flux_Nx: 2d,1-Hourly,Time-Averaged,Single-Level,Assimilation,Surface Flux Diagnostics V5.12.4.” doi:10.5067/7MCPBJ41Y0K6, https://disc.gsfc.nasa.gov/datasets/M2T1NXFLX_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_int_Nx: 2d,1-Hourly,Time-averaged,Single-Level,Assimilation,Vertically Integrated Diagnostics V5.12.4.” doi:10.5067/Q5GVUVUIVGO7, https://disc.gsfc.nasa.gov/datasets/M2T1NXINT_5.12.4/summary.

Pawson S (2020). “MERRA-2 tavg1_2d_lfo_Nx: 2d,1-Hourly,Time-Averaged,Single-Level,Assimilation,Land Surface Forcings V5.12.4.” doi:10.5067/L0T5GEG1NYFA, https://disc.gsfc.nasa.gov/datasets/M2T1NXLFO_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_lnd_Nx: 2d,1-Hourly,Time-Averaged,Single-Level,Assimilation,Land Surface Diagnostics V5.12.4.” doi:10.5067/RKPHT8KC1Y1T, https://disc.gsfc.nasa.gov/datasets/M2T1NXLND_5.12.4/summary.

- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_ocn_Nx: 2d,1-Hourly,Time-Averaged,Single-Level,Assimilation,Ocean Surface Diagnostics V5.12.4.” doi:10.5067/Y67YQ1L3ZZ4R, https://disc.gsfc.nasa.gov/datasets/M2T1NXOCN_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_rad_Nx: 2d,1-Hourly,Time-Averaged,Single-Level,Assimilation,Radiation Diagnostics V5.12.4.” doi:10.5067/Q9QMY5PBNV1T, https://disc.gsfc.nasa.gov/datasets/M2T1NXRAD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg1_2d_slv_Nx: 2d,1-Hourly,Time-Averaged,Single-Level,Assimilation,Single-Level Diagnostics V5.12.4.” doi:10.5067/VJAFPLIICSIV, https://disc.gsfc.nasa.gov/datasets/M2T1NXSLV_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_mst_Ne: 3d,3-Hourly,Time-Averaged,Model-Level Edge,Assimilation,Moist Processes Diagnostics V5.12.4.” doi:10.5067/JRUZ3SJ3ZJ72, https://disc.gsfc.nasa.gov/datasets/M2T3NEMST_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_trb_Ne: 3d,3-Hourly,Time-Averaged,Model-Level Edge,Assimilation,Turbulence Diagnostics V5.12.4.” doi:10.5067/4I7ZI35QRH8K, https://disc.gsfc.nasa.gov/datasets/M2T3NETRB_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_nav_Ne: 3d,3-Hourly,Time-Averaged, Vertical Coordinates V5.12.4.” doi:10.5067/N5WAKNS1UYQN, https://disc.gsfc.nasa.gov/datasets/M2T3NENAV_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_cld_Np: 3d,3-Hourly,Time-Averaged,Pressure-Level,Assimilation,Cloud Diagnostics V5.12.4.” doi:10.5067/TX10URJSKT53, https://disc.gsfc.nasa.gov/datasets/M2T3NPCLD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_mst_Np: 3d,3-Hourly,Time-Averaged,Pressure-Level,Assimilation,Moist Processes Diagnostics V5.12.4.” doi:10.5067/0TUFO90Q2PMS, https://disc.gsfc.nasa.gov/datasets/M2T3NPMST_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_rad_Np: 3d,3-Hourly,Time-Averaged,Pressure-Level,Assimilation,Radiation Diagnostics V5.12.4.” doi:10.5067/3UGE8WQXZAOK, https://disc.gsfc.nasa.gov/datasets/M2T3NPRAD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_tdt_Np: 3d,3-Hourly,Time-Averaged,Pressure-Level,Assimilation,Temperature Tendencies V5.12.4.” doi:10.5067/9NCR9DDDOPFI, https://disc.gsfc.nasa.gov/datasets/M2T3NPDT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_trb_Np: 3d,3-Hourly,Time-Averaged,Pressure-Level,Assimilation,Turbulence Diagnostics V5.12.4.” doi:10.5067/ZRRJPGWL8AVL, https://disc.gsfc.nasa.gov/datasets/M2T3NPTRB_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_udt_Np: 3d,3-Hourly,Time-Averaged,Pressure-Level,Assimilation,Wind Tendencies V5.12.4.” doi:10.5067/CWV0G3PPPFW, https://disc.gsfc.nasa.gov/datasets/M2T3NPUDT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_odt_Np: 3d,3-Hourly,Time-Averaged,Pressure-Level,Assimilation,Ozone Tendencies V5.12.4.” doi:10.5067/SOLYTK57786Z, https://disc.gsfc.nasa.gov/datasets/M2T3NPODT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_qdt_Np: 3d,3-Hourly,Time-Averaged,Pressure-Level,Assimilation,Moist Tendencies V5.12.4.” doi:10.5067/A9KWADY78YHQ, https://disc.gsfc.nasa.gov/datasets/M2T3NPQDT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_asm_Nv: 3d,3-Hourly,Time-Averaged,Model-Level,Assimilation,Assimilated Meteorological Fields V5.12.4.”

[doi:10.5067/SUOQESM06LPK](https://doi.org/10.5067/SUOQESM06LPK), https://disc.gsfc.nasa.gov/datasets/M2T3NVASM_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_cld_Nv: 3d,3-Hourly,Time-Averaged,Model-Level,Assimilation,Cloud Diagnostics V5.12.4.” [doi:10.5067/F9353J0FAHIH](https://doi.org/10.5067/F9353J0FAHIH), https://disc.gsfc.nasa.gov/datasets/M2T3NVCLD_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_mst_Nv: 3d,3-Hourly,Time-Averaged,Model-Level,Assimilation,Moist Processes Diagnostics V5.12.4.” [doi:10.5067/ZXTJ28TQR1TR](https://doi.org/10.5067/ZXTJ28TQR1TR), https://disc.gsfc.nasa.gov/datasets/M2T3NMST_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_3d_rad_Nv: 3d,3-Hourly,Time-Averaged,Model-Level,Assimilation,Radiation Diagnostics V5.12.4.” [doi:10.5067/7GFQKO1T43RW](https://doi.org/10.5067/7GFQKO1T43RW), https://disc.gsfc.nasa.gov/datasets/M2T3NVRAD_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavg3_2d_glc_Nx: 2d,3-Hourly,Time-Averaged,Single-Level,Assimilation,Land Ice Surface Diagnostics V5.12.4.” [doi:10.5067/9ETB4TT5J6US](https://doi.org/10.5067/9ETB4TT5J6US), https://disc.gsfc.nasa.gov/datasets/M2T3NXGLC_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instM_2d_asm_Nx: 2d,Monthly mean,Single-Level,Assimilation,Single-Level Diagnostics V5.12.4.” [doi:10.5067/5ESKGQTZG7FO](https://doi.org/10.5067/5ESKGQTZG7FO), https://disc.gsfc.nasa.gov/datasets/M2IMNXASM_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instM_2d_int_Nx: 2d,Monthly mean,Instantaneous,Single-Level,Assimilation,Vertically Integrated Diagnostics V5.12.4.” [doi:10.5067/KVTU1A8BWFSJ](https://doi.org/10.5067/KVTU1A8BWFSJ), https://disc.gsfc.nasa.gov/datasets/M2IMNXINT_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instM_2d_lfo_Nx: 2d,Monthly mean,Instantaneous,Single-Level,Assimilation,Land Surface Forcings V5.12.4.” [doi:10.5067/11F99Y6TXN99](https://doi.org/10.5067/11F99Y6TXN99), https://disc.gsfc.nasa.gov/datasets/M2IMNXLFO_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instM_2d_gas_Nx: 2d,Monthly mean,Instantaneous,Single-Level,Assimilation,Aerosol Optical Depth Analysis V5.12.4.” [doi:10.5067/XOGNBQEPLUC5](https://doi.org/10.5067/XOGNBQEPLUC5), https://disc.gsfc.nasa.gov/datasets/M2IMNXGAS_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instM_3d_asm_Np: 3d,Monthly mean,Instantaneous,Pressure-Level,Assimilation,Assimilated Meteorological Fields V5.12.4.” [doi:10.5067/2E096JV59PK7](https://doi.org/10.5067/2E096JV59PK7), https://disc.gsfc.nasa.gov/datasets/M2IMNPASM_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instM_3d_ana_Np: 3d,Monthly mean,Instantaneous,Pressure-Level,Analysis,Analyzed Meteorological Fields V5.12.4.” [doi:10.5067/V92O8XZ30XBI](https://doi.org/10.5067/V92O8XZ30XBI), https://disc.gsfc.nasa.gov/datasets/M2IMNPANA_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_adg_Nx: 2d,Monthly mean,Time-averaged,Single-Level,Assimilation,Aerosol Diagnostics (extended) V5.12.4.” [doi:10.5067/RZIK2TV7PP38](https://doi.org/10.5067/RZIK2TV7PP38), https://disc.gsfc.nasa.gov/datasets/M2TMNXADG_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_aer_Nx: 2d,Monthly mean,Time-averaged,Single-Level,Assimilation,Aerosol Diagnostics V5.12.4.” [doi:10.5067/FH9A0MLJPC7N](https://doi.org/10.5067/FH9A0MLJPC7N), https://disc.gsfc.nasa.gov/datasets/M2TMNXAER_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_chm_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Carbon Monoxide and Ozone Diagnostics V5.12.4.” [doi:10.5067/WMT31RKEXK8I](https://doi.org/10.5067/WMT31RKEXK8I), https://disc.gsfc.nasa.gov/datasets/M2TMNXCHM_5.12.4/summary.

- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_csp_Nx: 2d,Monthly mean,Time-averaged,Single-Level,Assimilation,COSP Satellite Simulator V5.12.4.” doi:10.5067/BZPOTGJOQKLU, https://disc.gsfc.nasa.gov/datasets/M2TMNXOSP_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_flux_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Surface Flux Diagnostics V5.12.4.” doi:10.5067/OJRLVL8YV2Y4, https://disc.gsfc.nasa.gov/datasets/M2TMNXFLX_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_int_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Vertically Integrated Diagnostics V5.12.4.” doi:10.5067/FQPTQ4OJ22TL, https://disc.gsfc.nasa.gov/datasets/M2TMNXINT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_ifo_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Land Surface Forcings V5.12.4.” doi:10.5067/5V7K6LJD44SY, https://disc.gsfc.nasa.gov/datasets/M2TMNXLFO_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_lnd_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Land Surface Diagnostics V5.12.4.” doi:10.5067/8S35XF81C28F, https://disc.gsfc.nasa.gov/datasets/M2TMXNLND_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_ocn_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Ocean Surface Diagnostics V5.12.4.” doi:10.5067/4IASLIDL8EEC, https://disc.gsfc.nasa.gov/datasets/M2TMNXOCN_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_rad_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Radiation Diagnostics V5.12.4.” doi:10.5067/OU3HJDS973O0, https://disc.gsfc.nasa.gov/datasets/M2TMNXRAD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_slv_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Single-Level Diagnostics V5.12.4.” doi:10.5067/APIB0BA5PD2K, https://disc.gsfc.nasa.gov/datasets/M2TMNXSLV_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_2d_glc_Nx: 2d,Monthly mean,Time-Averaged,Single-Level,Assimilation,Land Ice Surface Diagnostics V5.12.4.” doi:10.5067/5W8Q3I9WUFGX, https://disc.gsfc.nasa.gov/datasets/M2TMNXGLC_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_3d_cld_Np: 3d,Monthly mean,Time-Averaged,Pressure-Level,Assimilation,Cloud Diagnostics V5.12.4.” doi:10.5067/J9R0LXGH48JR, https://disc.gsfc.nasa.gov/datasets/M2TMNPCLD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_3d_mst_Np: 3d,Monthly mean,Time-Averaged,Pressure-Level,Assimilation,Moist Processes Diagnostics V5.12.4.” doi:10.5067/ZRZGD0DCK1CG, https://disc.gsfc.nasa.gov/datasets/M2TMNPMST_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_3d_rad_Np: 3d,Monthly mean,Time-Averaged,Pressure-Level,Assimilation,Radiation Diagnostics V5.12.4.” doi:10.5067/H3YGROBVBGFJ, https://disc.gsfc.nasa.gov/datasets/M2TMNPRAD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_3d_tdt_Np: 3d,Monthly mean,Time-Averaged,Pressure-Level,Assimilation,Temperature Tendencies V5.12.4.” doi:10.5067/VILT59HI2MOY, https://disc.gsfc.nasa.gov/datasets/M2TMNPTDT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_3d_trb_Np: 3d,Monthly mean,Time-Averaged,Pressure-Level,Assimilation,Turbulence Diagnostics V5.12.4.” doi:10.5067/2YOIQB5C3ACN, https://disc.gsfc.nasa.gov/datasets/M2TMNPTRB_5.12.4/summary.

- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_3d_ udt_ Np: 3d,Monthly mean,Time-Averaged,Pressure-Level,Assimilation,Wind Tendencies V5.12.4.” doi:10.5067/YSR6IA5057XX, https://disc.gsfc.nasa.gov/datasets/M2TMNPUOT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_3d_ odt_ Np: 3d,Monthly mean,Time-Averaged,Pressure-Level,Assimilation,Ozone Tendencies V5.12.4.” doi:10.5067/Z2KCWAV4GPD2, https://disc.gsfc.nasa.gov/datasets/M2TMNPODT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgM_3d_ qdt_ Np: 3d,Monthly mean,Time-Averaged,Pressure-Level,Assimilation,Moist Tendencies V5.12.4.” doi:10.5067/2ZTU87V69ATP, https://disc.gsfc.nasa.gov/datasets/M2TMNPQDT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 const_2d_ asm_ Nx: 2d, constants.” doi:10.5067/ME5QX6Q5IGGU, https://disc.gsfc.nasa.gov/datasets/M2C0NXASM_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instU_2d_ asm_ Nx: 2d,Diurnal,Instantaneous,Single-Level,Assimilation,Single-Level Diagnostics V5.12.4.” doi:10.5067/BOJSTZAO2L8R, https://disc.gsfc.nasa.gov/datasets/M2IUNXASM_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instU_2d_ int_ Nx: 2d,Diurnal,Instantaneous,Single-Level,Assimilation,Vertically Integrated Diagnostics V5.12.4.” doi:10.5067/DGAB3HFEYMLY, https://disc.gsfc.nasa.gov/datasets/M2IUNXINT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instU_2d_ lfo_ Nx: 2d,Diurnal,Instantaneous,Single-Level,Assimilation,Land Surface Forcings V5.12.4.” doi:10.5067/FC3BVJ88Y8A2, https://disc.gsfc.nasa.gov/datasets/M2IUNXLF0_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instU_2d_ gas_ Nx: 2d,Diurnal,Instantaneous,Single-Level,Assimilation,Aerosol Optical Depth Analysis V5.12.4.” doi:10.5067/TVJ4MHBED39L, https://disc.gsfc.nasa.gov/datasets/M2IUNXGAS_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instU_3d_ asm_ Np: 3d,Diurnal,Instantaneous,Pressure-Level,Assimilation,Assimilated Meteorological Fields V5.12.4.” doi:10.5067/6EGRBNEBMIYS, https://disc.gsfc.nasa.gov/datasets/M2IUNPASM_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 instU_3d_ ana_ Np: 3d,Diurnal,Instantaneous,Pressure-Level,Analysis,Analyzed Meteorological Fields V5.12.4.” doi:10.5067/TRD91YO9S6E7, https://disc.gsfc.nasa.gov/datasets/M2IUNPANA_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgU_2d_ adg_ Nx: 2d,Diurnal,Time-averaged,Single-Level,Assimilation,Aerosol Diagnostics (extended) V5.12.4.” doi:10.5067/YZJXZTFCX6B, https://disc.gsfc.nasa.gov/datasets/M2TUNXADG_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgU_2d_ aer_ Nx: 2d,Diurnal,Time-averaged,Single-Level,Assimilation,Aerosol Diagnostics V5.12.4.” doi:10.5067/KPUMVXFQLA1, https://disc.gsfc.nasa.gov/datasets/M2TUNXAER_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgU_2d_ chm_ Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Carbon Monoxide and Ozone Diagnostics V5.12.4.” doi:10.5067/5KFZ6GXRHZKN, https://disc.gsfc.nasa.gov/datasets/M2TUNXCHM_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgU_2d_ csp_ Nx: 2d,Diurnal,Time-averaged,Single-Level,Assimilation,COSP Satellite Simulator V5.12.4.” doi:10.5067/9PH5QU4CL9E8, https://disc.gsfc.nasa.gov/datasets/M2TUNXCSP_5.12.4/summary.

- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_2d_flux_Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Surface Flux Diagnostics V5.12.4." doi:10.5067/LUHPNWAKYIO3, https://disc.gsfc.nasa.gov/datasets/M2TUNXFLX_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_2d_int_Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Vertically Integrated Diagnostics V5.12.4." doi:10.5067/R2MPVU4EOSWT, https://disc.gsfc.nasa.gov/datasets/M2TUNXINT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_2d_lfo_Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Land Surface Forcings V5.12.4." doi:10.5067/BTSNKAJND3ME, https://disc.gsfc.nasa.gov/datasets/M2TUNXLFO_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_2d_lnd_Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Land Surface Diagnostics V5.12.4." doi:10.5067/W0J15047CF6N, https://disc.gsfc.nasa.gov/datasets/M2TUNXLND_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_2d_ocn_Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Ocean Surface Diagnostics V5.12.4." doi:10.5067/KLNAVGA7J66, https://disc.gsfc.nasa.gov/datasets/M2TUNXOCN_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_2d_rad_Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Radiation Diagnostics V5.12.4." doi:10.5067/4SDCJYK8P9QU, https://disc.gsfc.nasa.gov/datasets/M2TUNXRAD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_2d_slv_Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Single-Level Diagnostics V5.12.4." doi:10.5067/AFOK0TPEVQEK, https://disc.gsfc.nasa.gov/datasets/M2TUNXSLV_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_2d_glc_Nx: 2d,Diurnal,Time-Averaged,Single-Level,Assimilation,Land Ice Surface Diagnostics V5.12.4." doi:10.5067/7VUPQC736SWX, https://disc.gsfc.nasa.gov/datasets/M2TUNXGLC_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_3d_cld_Np: 3d,Diurnal,Time-Averaged,Pressure-Level,Assimilation,Cloud Diagnostics V5.12.4." doi:10.5067/EPW7T5UO0C0N, https://disc.gsfc.nasa.gov/datasets/M2TUNPCLD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_3d_mst_Np: 3d,Diurnal,Time-Averaged,Pressure-Level,Assimilation,Moist Processes Diagnostics V5.12.4." doi:10.5067/ZRSN0JU27DK2, https://disc.gsfc.nasa.gov/datasets/M2TUNPMST_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_3d_rad_Np: 3d,Diurnal,Time-Averaged,Pressure-Level,Assimilation,Radiation Diagnostics V5.12.4." doi:10.5067/H140JMDOWB0Y, https://disc.gsfc.nasa.gov/datasets/M2TUNPRAD_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_3d_tdt_Np: 3d,Diurnal,Time-Averaged,Pressure-Level,Assimilation,Temperature Tendencies V5.12.4." doi:10.5067/QPO9E5TPZ8OF, https://disc.gsfc.nasa.gov/datasets/M2TUNPTDT_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_3d_trb_Np: 3d,Diurnal,Time-Averaged,Pressure-Level,Assimilation,Turbulence Diagnostics V5.12.4." doi:10.5067/2A99C60CG7WC, https://disc.gsfc.nasa.gov/datasets/M2TUNPTRB_5.12.4/summary.
- Global Modeling And Assimilation Office, Pawson S (2015). "MERRA-2 tavgU_3d_udt_Np: 3d,Diurnal,Time-Averaged,Pressure-Level,Assimilation,Wind Tendencies V5.12.4." doi:10.5067/DO715T7T5PG8, https://disc.gsfc.nasa.gov/datasets/M2TUNPUTD_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgU_3d_odt_Np: 3d,Diurnal,Time-Averaged,Pressure-Level,Assimilation,Ozone Tendencies V5.12.4.” doi:10.5067/M8OJ09GZP23E, https://disc.gsfc.nasa.gov/datasets/M2TUNPODT_5.12.4/summary.

Global Modeling And Assimilation Office, Pawson S (2015). “MERRA-2 tavgU_3d_qdt_Np: 3d,Diurnal,Time-Averaged,Pressure-Level,Assimilation,Moist Tendencies V5.12.4.” doi:10.5067/S8HJXIR0BFTS, https://disc.gsfc.nasa.gov/datasets/M2TUNPQDT_5.12.4/summary.

Examples

```
download_merra2(
  collection = "inst1_2d_int_Nx",
  date = c("2024-01-01", "2024-01-01"),
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE
)
```

download_modis

Download MODIS product files

Description

Need maintenance for the directory path change in NASA EOSDIS. This function first retrieves the all hdf download links on a certain day, then only selects the relevant tiles from the retrieved links. Download is only done at the queried horizontal-vertical tile number combinations. An exception is MOD06_L2 product, which is produced every five minutes every day.

Usage

```
download_modis(
  product = c("MOD09GA", "MOD11A1", "MOD06_L2", "MCD19A2", "MOD13A2", "VNP46A2"),
  version = "61",
  horizontal_tiles = c(7, 13),
  vertical_tiles = c(3, 6),
  mod06_links = NULL,
  nasa_earth_data_token = NULL,
  date = c("2023-09-01", "2023-09-01"),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE
)
```

Arguments

product	character(1). One of c("MOD09GA", "MOD11A1", "MOD06_L2", "MCD19A2", "MOD13A2", "VNP46A2")
version	character(1). Default is "61", meaning v061.
horizontal_tiles	integer(2). Horizontal tile numbers c({start}, {end}). Default is c(7, 13).
vertical_tiles	integer(2). Vertical tile numbers c({start}, {end}). Default is c(3, 6).
mod06_links	character(1). CSV file path to MOD06_L2 download links from NASA LAADS MOD06_L2 . Default is NULL.
nasa_earth_data_token	character(1). Token for downloading data from NASA. Should be set before trying running the function.
date	character(2). length of 10 each. Start/end date for downloading data. Format "YYYY-MM-DD" (ex. January 1, 2018 = "2018-01-01"). Note: ignored if product == "MOD06_L2".
directory_to_save	character(1). Directory to save data.
acknowledgement	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
download	logical(1). Download data or only save wget commands.
remove_command	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

Value

NULL; HDF (.hdf) files will be stored in `directory_to_save`.

Note

Both dates in `date` should be in the same year. Directory structure looks like `input/modis/raw/{version}/{product}/{year}/{date}`.

Author(s)

Mitchell Manware, Insang Song

References

Lyapustin A, Wang Y (2022). "MODIS/Terra+Aqua Land Aerosol Optical Depth Daily L2G Global 1km SIN Grid V061." doi:10.5067/MODIS/MCD19A2.061, <https://lpdaac.usgs.gov/products/mcd19a2v061/>.

MODIS Atmosphere Science Team (2017). "MODIS/Terra Clouds 5-Min L2 Swath 1km and 5km." doi:10.5067/MODIS/MOD06_L2.061, https://ladsweb.modaps.eosdis.nasa.gov/missions-and-measurements/products/MOD06_L2.

Vermote E, Wolfe R (2021). “MODIS/Terra Surface Reflectance Daily L2G Global 1km and 500m SIN Grid V061.” doi:10.5067/MODIS/MOD09GA.061, <https://lpdaac.usgs.gov/products/mod09gav061/>.

Wan Z, Hook S, Hulley G (2021). “MODIS/Terra Land Surface Temperature/Emissivity Daily L3 Global 1km SIN Grid V061.” doi:10.5067/MODIS/MOD11A1.061, <https://lpdaac.usgs.gov/products/mod11a1v061/>.

Didan K (2021). “MODIS/Terra Vegetation Indices 16-Day L3 Global 1km SIN Grid V061.” doi:10.5067/MODIS/MOD13A2.061, <https://lpdaac.usgs.gov/products/mod13a2v061/>.

Román MO, Wang Z, Sun Q, Kalb V, Miller SD, Molthan A, Schultz L, Bell J, Stokes EC, Pandey B, Seto KC, Hall D, Oda T, Wolfe RE, Lin G, Golpayegani N, Devadiga S, Davidson C, Sarkar S, Praderas C, Schmaltz J, Boller R, Stevens J, Ramos González OM, Padilla E, Alonso J, Detrés Y, Armstrong R, Miranda I, Conte Y, Marrero N, MacManus K, Esch T, Masuoka EJ (2018). “NASA’s Black Marble nighttime lights product suite.” *Remote Sensing of Environment*, **210**, 113–143. ISSN 00344257, doi:10.1016/j.rse.2018.03.017, <https://linkinghub.elsevier.com/retrieve/pii/S003442571830110X>.

Examples

```
## Not run:
## NOTE: Examples are wrapped in `dontrun{}` to avoid sharing sensitive
##       NASA EarthData tokden information.
# example with MOD09GA product
download_modis(
  product = "MOD09GA",
  version = "61",
  horizontal_tiles = c(8, 8),
  vertical_tiles = c(4, 4),
  date = c("2024-01-01", "2024-01-01"),
  nasa_earth_data_token = "./pathtotoken/token.txt",
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE
)
# example with MOD06_L2 product
download_modis(
  product = "MOD06_L2",
  version = "61",
  horizontal_tiles = c(8, 8),
  vertical_tiles = c(4, 4),
  date = c("2024-01-01", "2024-01-01"),
  mod06_links =
    system.file(
      "extdata", "nasa", "LAADS_query.2024-08-02T12_49.csv",
      package = "amadeus"
    ),
  nasa_earth_data_token = "./pathtotoken/token.txt",
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE
)
```

```

)
# example with VNP46A2 product
download_modis(
  product = "VNP46A2",
  version = "61",
  horizontal_tiles = c(8, 8),
  vertical_tiles = c(4, 4),
  date = c("2024-01-01", "2024-01-01"),
  nasa_earth_data_token = "./pathtotoken/token.txt",
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE
)

## End(Not run)

```

download_narr

Download meteorological data

Description

The `download_narr` function accesses and downloads daily meteorological data from [NOAA's North American Regional Reanalysis \(NARR\) model](#).

Usage

```

download_narr(
  variables = NULL,
  year = c(2018, 2022),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE
)

```

Arguments

<code>variables</code>	character. Variable(s) name acronym. See List of Variables in NARR Files for variable names and acronym codes.
<code>year</code>	character(2). length of 4 each. Start/end years for downloading data.
<code>directory_to_save</code>	character(1). Directory(s) to save downloaded data files.
<code>acknowledgement</code>	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
<code>download</code>	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.

remove_command logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

Value

NULL; netCDF (.nc) files will be stored in directory_to_save.

Note

"Pressure levels" variables contain variable values at 29 atmospheric levels, ranging from 1000 hPa to 100 hPa. All pressure levels data will be downloaded for each variable.

Author(s)

Mitchell Manware, Insang Song

References

Mesinger F, DiMego G, Kalnay E, Mitchell K, Shafran PC, Ebisuzaki W, Jović D, Woollen J, Rogers E, Berbery EH, Ek MB, Fan Y, Grumbine R, Higgins W, Li H, Lin Y, Manikin G, Parrish D, Shi W (2006). "North American Regional Reanalysis." *Bulletin of the American Meteorological Society*, **87**(3), 343–360. ISSN 0003-0007, 1520-0477, doi:10.1175/BAMS873343.

Examples

```
download_narr(  
  variables = c("weasd", "omega"),  
  year = c(2023, 2023),  
  directory_to_save = tempdir(),  
  acknowledgement = TRUE,  
  download = FALSE, # NOTE: download skipped for examples,  
  remove_command = TRUE  
)
```

download_nei

Download road emissions data

Description

The download_nei() function accesses and downloads road emissions data from the [U.S Environmental Protection Agency's \(EPA\) National Emissions Inventory \(NEI\)](#).

Usage

```
download_nei(
  epa_certificate_path = system.file("extdata/cacert_gaftp_epa.pem", package = "amadeus"),
  certificate_url =
    "http://cacerts.digicert.com/DigiCertGlobalG2TLSRSA2562020CA1-1.crt",
  year = c(2017L, 2020L),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE,
  unzip = TRUE
)
```

Arguments

epa_certificate_path character(1). Path to the certificate file for EPA DataCommons. Default is 'ext-data/cacert_gaftp_epa.pem' under the package installation path.

certificate_url character(1). URL to certificate file. See notes for details.

year Available years of NEI data. Default is c(2017L, 2020L).

directory_to_save character(1). Directory to save data. Two sub-directories will be created for the downloaded zip files ("/zip_files") and the unzipped data files ("/data_files").

acknowledgement logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.

download logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.

remove_command logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

unzip logical(1). Unzip the downloaded zip files. Default is FALSE.

Value

NULL; Zip and/or data files will be downloaded and stored in respective sub-directories within `directory_to_save`.

Note

For EPA Data Commons certificate errors, follow the steps below:

1. Click Lock icon in the address bar at <https://gaftp.epa.gov>
2. Click Show Certificate
3. Access Details
4. Find URL with *.crt extension Currently we bundle the pre-downloaded crt and its PEM (which is accepted in wget command) file in `./inst/extdata`. The instruction above is for certificate updates in the future.

Author(s)

Ranadeep Daw, Insang Song

References

United States Environmental Protection Agency (2024). "Air Emissions Inventories." <https://www.epa.gov/air-emissions-inventories>.

Examples

```
download_nei(  
  year = c(2017L, 2020L),  
  directory_to_save = tempdir(),  
  acknowledgement = TRUE,  
  download = FALSE, # NOTE: download skipped for examples,  
  remove_command = TRUE,  
  unzip = FALSE  
)
```

download_nlcd	<i>Download land cover data</i>
---------------	---------------------------------

Description

The `download_nlcd()` function accesses and downloads land cover data from the [Multi-Resolution Land Characteristics \(MRLC\) Consortium's National Land Cover Database \(NLCD\) products data base](#).

Usage

```
download_nlcd(  
  collection = "Coterminous United States",  
  year = 2021,  
  directory_to_save = NULL,  
  acknowledgement = FALSE,  
  download = FALSE,  
  remove_command = FALSE,  
  unzip = TRUE,  
  remove_zip = FALSE  
)
```

Arguments

collection	character(1). "Coterminous United States" or "Alaska".
year	integer(1). Available years for Coterminous United States include 2001, 2004, 2006, 2008, 2011, 2013, 2016, 2019, and 2021. Available years for Alaska include 2001, 2011, and 2016.

directory_to_save	character(1). Directory to save data. Two sub-directories will be created for the downloaded zip files ("/zip_files") and the unzipped shapefiles ("/data_files").
acknowledgement	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
download	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
remove_command	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.
unzip	logical(1). Unzip zip files. Default is TRUE.
remove_zip	logical(1). Remove zip files from directory_to_download. Default is FALSE.

Value

NULL; Zip and/or data files will be downloaded and stored in respective sub-directories within directory_to_save.

Author(s)

Mitchell Manware, Insang Song

References

Dewitz J (2023). "National Land Cover Database (NLCD) 2021 Products." doi:10.5066/P9JZ7AO3.
 Dewitz J (2024). "National Land Cover Database (NLCD) 2019 Products (ver. 3.0, February 2024)." doi:10.5066/P9KZCM54.

Examples

```
download_nlcd(
  collection = "Coterminous United States",
  year = 2021,
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE,
  unzip = FALSE
)
```

download_prism

Download PRISM data

Description

Accesses and downloads Oregon State University's PRISM data from the PRISM Climate Group Web Service

Usage

```
download_prism(
  time,
  element = c("ppt", "tmin", "tmax", "tmean", "tdmean", "vpdmin", "vpdmax", "solslope",
    "soltotal", "solclear", "soltrans"),
  data_type = c("ts", "normals_800", "normals"),
  format = c("nc", "asc", "grib2"),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE
)
```

Arguments

time	<p>character(1). Length of 2, 4, 6, or 8. Time period for time series or normals. According to the PRISM Web Service Guide, acceptable formats include (disclaimer: the following is a direct quote; minimal formatting is applied): Time Series:</p> <ul style="list-style-type: none"> • YYYYMMDD for daily data (between yesterday and January 1st, 1981) – returns a single grid in a .zip file • YYYYMM for monthly data (between last month and January 1981) – returns a single grid in a .zip file • YYYY for annual data (between last year and 1981) - returns a single grid in a .zip file • YYYY for historical data (between 1980 and 1895) - returns a single zip file containing 12 monthly grids for YYYY plus the annual. <p>Normals:</p> <ul style="list-style-type: none"> • Monthly normal: date is MM (i.e., 04 for April) or the value 14, which returns the annual normal • Daily normal: date is MMDD (i.e., 0430 for April 30)
element	<p>character(1). Data element. One of c("ppt", "tmin", "tmax", "tmean", "tdmean", "vpdmin", "vpdmax") For normals, c("solslope", "soltotal", "solclear", "soltrans") are also accepted.</p>
data_type	<p>character(1). Data type.</p> <ul style="list-style-type: none"> • "ts": 4km resolution time series. • "normals_800": 800m resolution normals. • "normals": 4km resolution normals.
format	<p>character(1). Data format. Only applicable for data_type = "ts".</p>
directory_to_save	<p>character(1). Directory to download files.</p>
acknowledgement	<p>logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.</p>

download logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.

remove_command logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

Value

NULL; .bil (normals) or single grid files depending on the format choice will be stored in `directory_to_save`.

Author(s)

Insang Song

References

Daly C, Taylor GH, Gibson WP, Parzybok TW, Johnson GL, Pasteris PA (2000). "HIGH-QUALITY SPATIAL CLIMATE DATA SETS FOR THE UNITED STATES AND BEYOND." *Transactions of the ASAE*, **43**(6), 1957–1962. ISSN 2151-0059, doi:10.13031/2013.3101, <http://elibrary.asabe.org/abstract.asp??JID=3&AID=3101&CID=t2000&v=43&i=6&T=1>.

- [PRISM Climate Group](#)
- [PRISM Web Service Guide](#)

Examples

```
download_prism(
  time = "202104",
  element = "ppt",
  data_type = "ts",
  format = "nc",
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE
)
```

download_sedac_groads *Download roads data*

Description

The `download_sedac_groads()` function accesses and downloads roads data from [NASA's Global Roads Open Access Data Set \(gROADS\), v1 \(1980-2010\)](#).

Usage

```
download_sedac_groads(
  data_region = c("Americas", "Global", "Africa", "Asia", "Europe", "Oceania East",
    "Oceania West"),
  data_format = c("Shapefile", "Geodatabase"),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE,
  unzip = TRUE,
  remove_zip = FALSE
)
```

Arguments

data_region character(1). Data can be downloaded for "Global", "Africa", "Asia", "Europe", "Americas", "Oceania East", and "Oceania West".

data_format character(1). Data can be downloaded as "Shapefile" or "Geodatabase". (Only "Geodatabase" available for "Global" region).

directory_to_save character(1). Directory to save data. Two sub-directories will be created for the downloaded zip files ("/zip_files") and the unzipped shapefiles ("/data_files").

acknowledgement logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.

download logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.

remove_command logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

unzip logical(1). Unzip zip files. Default is TRUE.

remove_zip logical(1). Remove zip files from directory_to_download. Default is FALSE.

Value

NULL; Zip and/or data files will be downloaded and stored in respective sub-directories within directory_to_save.

Author(s)

Mitchell Manware, Insang Song

References

Center For International Earth Science Information Network-CIESIN-Columbia University, Information Technology Outreach Services-ITOS-University Of Georgia (2013). "Global Roads Open Access Data Set, Version 1 (gROADSv1)." doi:10.7927/H4VD6WCT, <https://sedac.ciesin.columbia.edu/data/set/groads-global-roads-open-access-v1>.

Examples

```
download_sedac_groads(
  data_region = "Americas",
  data_format = "Shapefile",
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE,
  unzip = FALSE
)
```

```
download_sedac_population
```

Download population density data

Description

The `download_sedac_population()` function accesses and downloads population density data from [NASA's UN WPP-Adjusted Population Density, v4.11](#).

Usage

```
download_sedac_population(
  data_resolution = "60 minute",
  data_format = c("GeoTIFF", "ASCII", "netCDF"),
  year = "2020",
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE,
  unzip = TRUE,
  remove_zip = FALSE
)
```

Arguments

<code>data_resolution</code>	character(1). Available resolutions are 30 second (approx. 1 km), 2.5 minute (approx. 5 km), 15 minute (approx. 30 km), 30 minute (approx. 55 km), and 60 minute (approx. 110 km).
<code>data_format</code>	character(1). Individual year data can be downloaded as "ASCII" or "GeoTIFF". "all" years is downloaded as "netCDF".
<code>year</code>	character(1). Available years are 2000, 2005, 2010, 2015, and 2020, or "all" for all years.
<code>directory_to_save</code>	character(1). Directory to save data. Two sub-directories will be created for the downloaded zip files ("/zip_files") and the unzipped shapefiles ("/data_files").

acknowledgement	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
download	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
remove_command	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.
unzip	logical(1). Unzip zip files. Default is TRUE.
remove_zip	logical(1). Remove zip files from directory_to_download. Default is FALSE.

Value

NULL; Zip and/or data files will be downloaded and stored in respective sub-directories within directory_to_save.

Author(s)

Mitchell Manware, Insang Song

References

Center For International Earth Science Information Network-CIESIN-Columbia University (2017). "Gridded Population of the World, Version 4 (GPWv4): Population Density, Revision 11." doi:10.7927/H49C6VHW, <https://sedac.ciesin.columbia.edu/data/set/gpw-v4-population-density-rev11>.

Examples

```
download_sedac_population(
  data_resolution = "30 second",
  data_format = "GeoTIFF",
  year = "2020",
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE,
  unzip = FALSE
)
```

download_terraclimate *Download TerraClimate data*

Description

The download_terraclimate function accesses and downloads climate and water balance data from the [University of California Merced Climatology Lab's TerraClimate dataset](#).

Usage

```
download_terraclimate(
  variables = NULL,
  year = c(2018, 2022),
  directory_to_save = NULL,
  acknowledgement = FALSE,
  download = FALSE,
  remove_command = FALSE
)
```

Arguments

variables	character(1). Variable(s) name(s). See TerraClimate Direct Downloads for variable names and acronym codes.
year	character(2). length of 4 each. Start/end years for downloading data.
directory_to_save	character(1). Directory(s) to save downloaded data files.
acknowledgement	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
download	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
remove_command	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

Value

NULL; netCDF (.nc) files will be stored in a variable-specific folder within `directory_to_save`.

Author(s)

Mitchell Manware, Insang Song

References

Abatzoglou JT, Dobrowski SZ, Parks SA, Hegewisch KC (2018). “TerraClimate, a high-resolution global dataset of monthly climate and climatic water balance from 1958–2015.” *Scientific data*, **5**(1), 1–12.

Examples

```
download_terraclimate(
  variables = "Precipitation",
  year = c(2023, 2023),
  directory_to_save = tempdir(),
  acknowledgement = TRUE,
  download = FALSE, # NOTE: download skipped for examples,
  remove_command = TRUE
)
```

download_tri	<i>Download toxic release data</i>
--------------	------------------------------------

Description

The `download_tri()` function accesses and downloads toxic release data from the [U.S. Environmental Protection Agency's \(EPA\) Toxic Release Inventory \(TRI\) Program](#).

Usage

```
download_tri(  
  year = c(2018L, 2022L),  
  directory_to_save = NULL,  
  acknowledgement = FALSE,  
  download = FALSE,  
  remove_command = FALSE  
)
```

Arguments

<code>year</code>	character(2). length of 4 each. Start/end years for downloading data.
<code>directory_to_save</code>	character(1). Directory to download files.
<code>acknowledgement</code>	logical(1). By setting TRUE the user acknowledges that the data downloaded using this function may be very large and use lots of machine storage and memory.
<code>download</code>	logical(1). FALSE will generate a *.txt file containing all download commands. By setting TRUE the function will download all of the requested data files.
<code>remove_command</code>	logical(1). Remove (TRUE) or keep (FALSE) the text file containing download commands.

Value

NULL; Comma-separated value (CSV) files will be stored in `directory_to_save`.

Author(s)

Mariana Kassien, Insang Song

References

United States Environmental Protection Agency (2024). "TRI Basic Data Files: Calendar Years 1987 – Present." <https://www.epa.gov/toxics-release-inventory-tri-program/tri-data-action-0>.

Examples

```
download_tri(  
  year = c(2021L, 2021L),  
  directory_to_save = tempdir(),  
  acknowledgement = TRUE,  
  download = FALSE, # NOTE: download skipped for examples,  
  remove_command = TRUE  
)
```

dt_as_mysftime	<i>Convert a data.table to an sftime</i>
----------------	--

Description

Convert a `data.table` object to an `sftime`. `x` must be a `data.table` object with "lon", "lat", and "time" columns to describe the longitude, latitude, and time-orientation, respectively, of `x`.

Usage

```
dt_as_mysftime(x, lonname, latname, timename, crs)
```

Arguments

<code>x</code>	a <code>data.table</code>
<code>lonname</code>	character for longitude column name
<code>latname</code>	character for latitude column name
<code>timename</code>	character for time column name
<code>crs</code>	coordinate reference system

Value

an `sftime` object

Author(s)

Eva Marques

`generate_date_sequence`*Generate date sequence*

Description

Generate a sequence of dates from `date_start` to `date_end`.

Usage

```
generate_date_sequence(date_start, date_end, sub_hyphen = TRUE)
```

Arguments

<code>date_start</code>	character(1). Beginning of date sequence.
<code>date_end</code>	character(1). End of date sequence.
<code>sub_hyphen</code>	logical(1). Substitute hyphen in dates. If TRUE, returns date sequence as "YYYYM-MDD". If FALSE, returns date sequence as "YYYY-MM-DD".

Value

vector

`generate_time_sequence`*Generate time sequence*

Description

Generate a sequence of time values based on the GEOS-CF collection.

Usage

```
generate_time_sequence(collection)
```

Arguments

<code>collection</code>	character(1). GEOS-CF data collection
-------------------------	---------------------------------------

Value

vector

Note

GEOS-CF hourly values are observed on the hour (ie. 0000 = 12:00:00 AM, 0100 = 01:00:00 AM) or the half hour (ie. 0030 = 12:30:00 AM, 0130 = 01:30:00 AM). Typically, 2-dimensional collections (latitude and longitude only) utilize half hour, and 3-dimensional collections (latitude, longitude, and time) utilize hour.

narr_variable	<i>Sort NOAA NARR variables</i>
---------------	---------------------------------

Description

Determine whether a NOAA NARR variable selected for download is a monolevel or pressure level variable. Monolevel variables are derived from <https://downloads.psl.noaa.gov/Datasets/NARR/Dailies/monolevel/>, and pressure level variables are derived from <https://downloads.psl.noaa.gov//Datasets/NARR/Dailies/pressure/>.

Usage

```
narr_variable(variable)
```

Arguments

variable	character(1). User-selected NARR variable
----------	---

Value

list with URL base and vector of months (blank for monolevel)

process_aqs	<i>Process U.S. EPA AQS daily CSV data</i>
-------------	--

Description

The `process_aqs()` function cleans and imports raw air quality monitoring sites from pre-generated daily CSV files, returning a single `SpatVector` or `sf` object. `date` is used to filter the raw data read from csv files. Filtered rows are then processed according to `mode` argument. Some sites report multiple measurements per day with and without **exceptional events** the internal procedure of this function keeps "Included" if there are multiple event types per site-time.

Usage

```
process_aqs(
  path = NULL,
  date = c("2018-01-01", "2022-12-31"),
  mode = c("date-location", "available-data", "location"),
  data_field = "Arithmetic.Mean",
  return_format = c("terra", "sf", "data.table"),
  extent = NULL,
  ...
)
```

Arguments

path	character(1). Directory path to daily measurement data.
date	character(2). Start and end date. Should be in "YYYY-MM-DD" format and sorted.
mode	character(1). One of <ul style="list-style-type: none"> • "date-location" (all dates * all locations) • "available-data" (date-location pairs with available data) • "location" (unique locations).
data_field	character(1). Data field to extract.
return_format	character(1). "terra" or "sf" or "data.table".
extent	numeric(4). Spatial extent of the resulting object. The order should be c(xmin, xmax, ymin, ymax). The coordinate system should be WGS84 (EPSG:4326).
...	Placeholders.

Value

a SpatVector, sf, or data.table object depending on the return_format

Note

Choose date and mode values with caution. The function may return a massive data.table depending on the time range, resulting in a long processing time or even a crash if data is too large for your computing environment to process.

See Also

- [download_aqs\(\)](#)
- [EPA, n.d., AQS Parameter Codes](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
aqs <- process_aqs(
  path = "../data/aqs_daily_example.csv",
```

```

    date = c("2022-12-01", "2023-01-31"),
    mode = "full",
    return_format = "terra"
)

## End(Not run)

```

process_blackmarble *Assign VIIRS Black Marble products corner coordinates to retrieve a merged raster*

Description

This function will return a SpatRaster object with georeferenced h5 files of Black Marble product. Referencing corner coordinates are necessary as the original h5 data do not include such information.

Usage

```

process_blackmarble(
  path = NULL,
  date = NULL,
  tile_df = process_blackmarble_corners(),
  subdataset = 3L,
  crs = "EPSG:4326",
  ...
)

```

Arguments

path	character. Full paths of h5 files.
date	character(1). Date to query.
tile_df	data.frame. Contains four corner coordinates in fields named c("xmin", "xmax", "ymin", "ymax"). See process_blackmarble_corners to generate a valid object for this argument.
subdataset	integer(1). Subdataset number to process. Default is 3L.
crs	character(1). terra::crs compatible CRS. Default is "EPSG:4326"
...	For internal use.

Value

a SpatRaster object

Author(s)

Insang Song

References

- Wang, Z. (2022). Black Marble User Guide (Version 1.3). NASA.

See Also

- [terra::describe](#)
- [terra::merge](#)
- [process_blackmarble_corners](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
vnp46a2 <- process_blackmarble(
  path =
    list.files("./data", pattern = "VNP46A2.", full.names = TRUE),
  date = "2024-01-01",
  tile_df =
    process_blackmarble_corners(hrangle = c(8, 10), vrangle = c(4, 5)),
  subdataset = 3L,
  crs = "EPSG:4326"
)

## End(Not run)
```

```
process_blackmarble_corners
  Process Black Marble corners
```

Description

Tile corner generator for Black Marble products.

Black Marble products are in HDF5 format and are read without georeference with typical R geospatial packages. This function generates a data.frame of corner coordinates for assignment.

Usage

```
process_blackmarble_corners(hrangle = c(5, 11), vrangle = c(3, 6))
```

Arguments

```
hrangle      integer(2). Both should be in 0-35.
vrangle      integer(2). Both should be in 0-17.
```

Value

data.frame with xmin, xmax, ymin, and ymax fields

Author(s)

Insang Song

References

- Wang, Z. (2022). Black Marble User Guide (Version 1.3). NASA.

Examples

```
process_blackmarble_corners(hrangle = c(1, 2), vrangle = c(1, 2))
```

process_collection *Process GEOS-CF and MERRA2 collection codes*

Description

Identify the GEOS-CF or MERRA2 collection based on the file path.

Usage

```
process_collection(
  path,
  source,
  collection = FALSE,
  date = FALSE,
  datetime = FALSE
)
```

Arguments

path	character(1). File path to data file.
source	character(1). "geos" for GEOS-CF or "merra2" for MERRA2
collection	logical(1). Identifies and returns collection name(s) based on provided file path(s).
date	logical(1). Identifies and returns date sequence (YYYYMMDD) based on provided file path(s).
datetime	logical(1). Identifies and returns date time sequence (YYYYMoMoDDHH-MiMi) based on provided file path(s).

Value

character

process_conformity *Check input assumptions*

Description

Check if all of "lon", "lat", and "time" (only if check_time = TRUE) then convert inputs into a SpatVector object.

Usage

```
process_conformity(locs = NULL, check_time = FALSE, locs_epsg = "EPSG:4326")
```

Arguments

locs	Data. sf , SpatVector , or data.frame
check_time	logical(1). Whether "time" exists in column names.
locs_epsg	character(1). "{authority}:{code}" or Well-Known Text format for coordinate reference system definition.

Value

a SpatVector object

Author(s)

Insang Song

process_covariates *Process raw data wrapper function*

Description

This function processes raw data files which have been downloaded by [download_data](#). process_covariates and the underlying source-specific processing functions have been designed to operate on the raw data files. To avoid errors, **do not edit the raw data files before passing to process_covariates**.

Usage

```
process_covariates(
  covariate = c("modis_swath", "modis_merge", "koppen-geiger", "blackmarble",
    "koeppen-geiger", "koppen", "koeppen", "geos", "dummies", "gmted", "hms", "smoke",
    "sedac_population", "population", "sedac_groads", "groads", "roads", "nlcd", "tri",
    "narr", "nei", "ecoregions", "ecoregion", "merra", "merra2", "gridmet",
    "terraclimate", "huc", "cropscape", "cdl", "prism"),
  path = NULL,
  ...
)
```

Arguments

covariate	character(1). Covariate type.
path	character(1). Directory or file path to raw data depending on covariate value.
...	Arguments passed to each raw data processing function.

Value

SpatVector, SpatRaster, sf, or character depending on covariate type and selections.

Author(s)

Insang Song

See Also

- [process_modis_swath](#): "modis_swath"
- [process_modis_merge](#): "modis_merge"
- [process_blackmarble](#): "blackmarble"
- [process_koppen_geiger](#): "koppen-geiger", "koeppen-geiger", "koppen"
- [process_ecoregion](#): "ecoregion", "ecoregions"
- [process_nlcd](#): "nlcd", "NLCD"
- [process_tri](#): "tri", "TRI"
- [process_nei](#): "nei", "NEI"
- [process_geos](#): "geos", "GEOS"
- [process_gmted](#): "gmted", "GMTED"
- [process_aqs](#): "aqs", "AQS"
- [process_hms](#): "hms", "smoke", "HMS"
- [process_narr](#): "narr", "NARR"
- [process_sedac_groads](#): "sedac_groads", "roads", "groads"
- [process_sedac_population](#): "sedac_population", "population"
- [process_merra2](#): "merra", "merra2", "MERRA2"
- [process_gridmet](#): "gridmet", "gridMET"
- [process_terraclimate](#): "terraclimate", "TerraClimate"
- [process_huc](#): "huc", "HUC"
- [process_cropscape](#): "cropscape", "cdl"
- [process_prism](#): "prism", "PRISM"

Examples

```
## NOTE: Example is wrapped in \dontrun{} as function requires a large
## amount of data which is not included in the package.
## Not run:
process_covariates(
  covariate = "narr",
  date = c("2018-01-01", "2018-01-01"),
  variable = "weasd",
  path = system.file("extdata", "examples", "narr", "weasd")
)

## End(Not run)
```

process_cropscape	<i>Process CropScape data</i>
-------------------	-------------------------------

Description

This function imports and cleans raw CropScape data, returning a single SpatRaster object.

Reads CropScape file of selected year.

Usage

```
process_cropscape(path = NULL, year = 2021, extent = NULL, ...)
```

Arguments

path	character giving CropScape data path
year	numeric giving the year of CropScape data used
extent	numeric(4) or SpatExtent giving the extent of the raster if NULL (default), the entire raster is loaded
...	Placeholders.

Value

a SpatRaster object

Author(s)

Insang Song

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
cropscape <- process_cropscape(
  path = "../data/cropscape_example.tif",
  year = 2020
)

## End(Not run)
```

process_ecoregion	<i>Process ecoregion data</i>
-------------------	-------------------------------

Description

The `process_ecoregion` function imports and cleans raw ecoregion data, returning a `SpatVector` object.

Usage

```
process_ecoregion(path = NULL, extent = NULL, ...)
```

Arguments

path	character(1). Path to Ecoregion Shapefiles
extent	numeric(4) or <code>SpatExtent</code> giving the extent of the raster if <code>NULL</code> (default), the entire raster is loaded
...	Placeholders.

Value

a `SpatVector` object

Note

The function will fix Tukey's bridge in Portland, ME. This fix will ensure that the EPA air quality monitoring sites will be located within the ecoregion.

Author(s)

Insang Song

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
ecoregion <- process_ecoregion(
  path = "../data/epa_ecoregion.gpkg"
)

## End(Not run)
```

process_flatten_sds *Process MODIS layers*

Description

Aggregate layers in a sub-dataset in sinusoidal MODIS products.

Some MODIS products consist of multi-layer subdatasets. This function aggregates multiple layers into single layer SpatRaster. `fun_agg` is applied at overlapping cells.

Usage

```
process_flatten_sds(path = NULL, subdataset = NULL, fun_agg = "mean", ...)
```

Arguments

<code>path</code>	character(1). Full path to MODIS HDF4/HDF5 file. Direct sub-dataset access is supported, for example, <code>HDF4_EOS:EOS_GRID:{filename}:{base_grid_information}:{subdataset}</code>
<code>subdataset</code>	character(1). Exact or regular expression filter of sub-dataset. See process_modis_sds for details.
<code>fun_agg</code>	character(1). Function name to aggregate layers. Should be acceptable to terra::tapp .
<code>...</code>	Placeholders.

Value

a SpatRaster object

Note

HDF values are read as original without scaling. Users should consult MODIS product documentation to apply proper scaling factor for post-hoc adjustment. If users have no preliminary information about MODIS sub-datasets, consider running `terra::describe(__filename__, sds = TRUE)` to navigate the full list of sub-datasets in the input file then consult the documentation of MODIS product.

Author(s)

Insang Song

See Also

[terra::tapp](#), [terra::rast](#), [terra::describe](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
##       amount of data which is not included in the package.
## Not run:
mod09ga_flatten <- process_flatten_sds(
  path =
    list.files("./data", pattern = "MOD09GA.", full.names = TRUE)[1],
  subdataset = process_modis_sds("MOD09GA"),
  fun_agg = "mean"
)

## End(Not run)
```

process_geos

Process atmospheric composition data

Description

The `process_geos()` function imports and cleans raw atmospheric composition data, returning a single `SpatRaster` object.

Usage

```
process_geos(
  date = c("2018-01-01", "2018-01-01"),
  variable = NULL,
  path = NULL,
  extent = NULL,
  ...
)
```

Arguments

<code>date</code>	character(2). length of 10. Format "YYYY-MM-DD".
<code>variable</code>	character(1). GEOS-CF variable name(s).
<code>path</code>	character(1). Directory with downloaded netCDF (.nc4) files.
<code>extent</code>	numeric(4) or <code>SpatExtent</code> giving the extent of the raster if NULL (default), the entire raster is loaded
<code>...</code>	Placeholders.

Value

a SpatRaster object;

Note

Layer names of the returned SpatRaster object contain the variable, pressure level, date, and hour.

Author(s)

Mitchell Manware

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
geos <- process_geos(
  date = c("2024-01-01", "2024-01-10"),
  variable = "03",
  path = "../data/aqc_tavg_1hr_g1440x721_v1"
)

## End(Not run)
```

process_gmted

Process elevation data

Description

The process_gmted() function imports and cleans raw elevation data, returning a single SpatRaster object.

Usage

```
process_gmted(variable = NULL, path = NULL, extent = NULL, ...)
```

Arguments

variable	vector(1). Vector containing the GMTED statistic first and the resolution second. (Example: variable = c("Breakline Emphasis", "7.5 arc-seconds")). <ul style="list-style-type: none"> Statistic options: "Breakline Emphasis", "Systematic Subsample", "Median Statistic", "Minimum Statistic", "Mean Statistic", "Maximum Statistic", "Standard Deviation Statistic" Resolution options: "30 arc-seconds", "15 arc-seconds", "7.5 arc-seconds"
path	character(1). Directory with downloaded GMTED "*_grd" folder containing .adf files.
extent	numeric(4) or SpatExtent giving the extent of the raster if NULL (default), the entire raster is loaded
...	Placeholders.

Value

a SpatRaster object

Note

SpatRaster layer name indicates selected variable and resolution, and year of release (2010).

Author(s)

Mitchell Manware

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
gmted <- process_gmted(
  variable = c("Breakline Emphasis", "7.5 arc-seconds"),
  path = "../data/be75_grd"
)

## End(Not run)
```

process_gmted_codes *Process elevation statistic and resolution codes*

Description

Identify the GMTED statistic and resolution based on the file path. Convert statistic and resolution to/from full string to/from statistic and resolution code.

Usage

```
process_gmted_codes(
  string,
  statistic = FALSE,
  resolution = FALSE,
  invert = FALSE
)
```

Arguments

string	character(1). File path to GMTED data file.
statistic	logical(1). Matches statistic to statistic code.
resolution	logical(1). Matches resolution to resolution code.
invert	logical(1). Default = FALSE. invert = TRUE assumes string provides statistic or resolution code, and returns full length statistic or resolution.

Value

character

process_gridmet	<i>Process gridMET data</i>
-----------------	-----------------------------

Description

The process_gridmet() function imports and cleans raw gridded surface meteorological data, returning a single SpatRaster object.

Usage

```
process_gridmet(
  date = c("2023-09-01", "2023-09-01"),
  variable = NULL,
  path = NULL,
  extent = NULL,
  ...
)
```

Arguments

date	character(2). length of 10 each. Start/end date of downloaded data. Format YYYY-MM-DD (ex. September 1, 2023 = "2023-09-01").
variable	character(1). Variable name or acronym code. See gridMET Generate Wget File for variable names and acronym codes. (Note: variable "Burning Index" has code "bi" and variable "Energy Release Component" has code "erc").
path	character(1). Directory with downloaded netCDF (.nc) files.
extent	numeric(4) or SpatExtent giving the extent of the raster if NULL (default), the entire raster is loaded
...	Placeholders.

Value

a SpatRaster object

Note

Layer names of the returned SpatRaster object contain the variable acronym, and date.

Author(s)

Mitchell Manware

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
gridmet <- process_gridmet(
  date = c("2023-01-01", "2023-01-10"),
  variable = "Precipitation",
  path = "./data/pr"
)

## End(Not run)
```

process_gridmet_codes *Process gridMET variable codes*

Description

Convert gridMET variable names to/from variable codes.

Usage

```
process_gridmet_codes(string, invert = FALSE)
```

Arguments

string	character(1). gridMET variable name or variable code.
invert	logical(1). Default = FALSE. invert = TRUE assumes string provides variable code and returns full length variable name.

Value

character

process_hms *Process wildfire smoke data*

Description

The process_hms() function imports and cleans raw wildfire smoke plume coverage data, returning a single SpatVector object.

Usage

```
process_hms(
  date = c("2018-01-01", "2018-01-01"),
  path = NULL,
  extent = NULL,
  ...
)
```

Arguments

date	character(2). length of 10 each. Start/end date of downloaded data. Format YYYY-MM-DD (ex. September 1, 2023 = "2023-09-01").
path	character(1). Directory with downloaded NOAA HMS data files.
extent	numeric(4) or SpatExtent giving the extent of the output if NULL (default), the entire data is returned
...	Placeholders.

Value

a SpatVector or character object

Note

process_hms() will return a character object if there are no wildfire smoke plumes present for the selected dates and density. The returned character will contain the density value and the sequence of dates for which no wildfire smoke plumes were detected (see "Examples"). If multiple density polygons overlap, the function will return the highest density value.

Author(s)

Mitchell Manware

Examples

```
hms <- process_hms(
  date = c("2018-12-30", "2019-01-01"),
  path = "../tests/testdata/hms/"
)
```

process_huc

Retrieve Hydrologic Unit Code (HUC) data

Description

Retrieve Hydrologic Unit Code (HUC) data

Usage

```
process_huc(
  path,
  layer_name = NULL,
  huc_level = NULL,
  huc_header = NULL,
  extent = NULL,
  ...
)
```

Arguments

path	character. Path to the file or the directory containing HUC data.
layer_name	character(1). Layer name in the path
huc_level	character(1). Field name of HUC level
huc_header	character(1). The upper level HUC code header to extract lower level HUCs.
extent	numeric(4) or SpatExtent giving the extent of the raster if NULL (default), the entire raster is loaded
...	Arguments passed to <code>nhdplusTools::get_huc()</code>

Value

a SpatVector object

Author(s)

Insang Song

See Also

[nhdplusTools::get_huc](#)

Examples

```
## NOTE: Examples are wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
library(terra)
getf <- "WBD_National_GDB.gdb"
# check the layer name to read
terra::vector_layers(getf)
test1 <- process_huc(
  getf,
  layer_name = "WBDHU8",
  huc_level = "huc8"
)
test2 <- process_huc(
  getf,
  layer_name = "WBDHU8",
```

```
    huc_level = "huc8"
  )
test3 <- process_huc(
  "",
  layer_name = NULL,
  huc_level = NULL,
  huc_header = NULL,
  id = "030202",
  type = "huc06"
)

## End(Not run)
```

process_koppen_geiger *Process climate classification data*

Description

The `process_koppen_geiger()` function imports and cleans raw climate classification data, returning a single `SpatRaster` object.

Usage

```
process_koppen_geiger(path = NULL, extent = NULL, ...)
```

Arguments

<code>path</code>	character(1). Path to Koppen-Geiger climate zone raster file
<code>extent</code>	numeric(4) or <code>SpatExtent</code> giving the extent of the raster if <code>NULL</code> (default), the entire raster is loaded
<code>...</code>	Placeholders.

Value

a `SpatRaster` object

Author(s)

Insang Song

Examples

```
## NOTE: Example is wrapped in \dontrun{} as function requires a large
## amount of data which is not included in the package.
## Not run:
kg <- process_koppen_geiger(
  path = "../data/koppen_geiger_data.tif"
)

## End(Not run)
```

process_merra2	<i>Process meteorological and atmospheric data</i>
----------------	--

Description

The `process_merra2()` function imports and cleans raw atmospheric composition data, returning a single `SpatRaster` object.

Usage

```
process_merra2(  
  date = c("2018-01-01", "2018-01-01"),  
  variable = NULL,  
  path = NULL,  
  extent = NULL,  
  ...  
)
```

Arguments

date	character(2). length of 10. Format "YYYY-MM-DD".
variable	character(1). MERRA2 variable name(s).
path	character(1). Directory with downloaded netCDF (.nc4) files.
extent	numeric(4) or <code>SpatExtent</code> giving the extent of the raster if <code>NULL</code> (default), the entire raster is loaded
...	Placeholders.

Value

a `SpatRaster` object;

Note

Layer names of the returned `SpatRaster` object contain the variable, pressure level, date, and hour. Pressure level values utilized for layer names are taken directly from raw data and are not edited to retain pressure level information.

Author(s)

Mitchell Manware

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
merra2 <- process_merra2(
  date = c("2024-01-01", "2024-01-10"),
  variable = "CPT",
  path = "./data/inst1_2d_int_Nx"
)

## End(Not run)
```

process_merra2_time *Process MERRA2 time steps*

Description

Identify the time step of data observations based on MERRA2 collection and filter to time values in from.

Usage

```
process_merra2_time(collection, from)
```

Arguments

collection character(1). MERRA2 collection name.
 from SpatRaster(1). Object to extract time values from.

Value

character

process_modis_merge *Process MODIS .hdf files*

Description

Get mosaicked or merged raster from multiple MODIS hdf files.

Usage

```
process_modis_merge(
  path = NULL,
  date = NULL,
  subdataset = NULL,
  fun_agg = "mean",
  ...
)
```

Arguments

path	character. Full list of hdf file paths. preferably a recursive search result from base::list.files .
date	character(1). date to query. Should be in "YYYY-MM-DD" format.
subdataset	character(1). subdataset names to extract. Should conform to regular expression. See base::regex for details. Default is NULL, which will result in errors. Users should specify which subdatasets will be imported.
fun_agg	Function name or custom function to aggregate overlapping cell values. See fun description in terra::tapp for details.
...	For internal use.

Value

a SpatRaster object

Note

Curvilinear products (i.e., swaths) will not be accepted. MODIS products downloaded by functions in [amadeus](#), [MODISTools](#), and [luna](#) are accepted.

Author(s)

Insang Song

See Also

[download_data](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
mod09ga_merge <- process_modis_merge(
  path =
    list.files("./data", pattern = "MOD09GA.", full.names = TRUE),
  date = "2024-01-01",
  subdataset = "sur_refl_b01_1",
  fun_agg = "mean"
)

## End(Not run)
```

process_modis_sds *Process MODIS sub-datasets*

Description

Selected MODIS sinusoidal grid product subdataset name selector. Four presets are supported. `custom_sel` supersedes presets of product values.

Usage

```
process_modis_sds(  
  product = c("MOD11A1", "MOD13A2", "MOD09GA", "MCD19A2"),  
  custom_sel = NULL,  
  ...  
)
```

Arguments

<code>product</code>	character(1). Product code.
<code>custom_sel</code>	character(1). Custom filter. If this value is not NULL, preset filter is overridden.
<code>...</code>	Placeholders.

Value

A character object that conforms to the regular expression. Details of regular expression in R can be found in [regex](#).

Note

Preset product codes and associated variables include

- "MOD11A1" - Land surface temperature (LST)
- "MOD13A2" - Normalized Difference Vegetation Index (NDVI)
- "MOD09GA" - Surface reflectance, and
- "MCD19A2" - Aerosol optical depth (AOD).

For a full list of available MODIS product codes, see the "Short Name" column at [NASA LP DAAC Search Data Catalog](#). When utilizing a product code from this "Short Name" column, **do not include** the version number following the period. For example, if "Short Name" = MCD12C1.006, then `product = "MCD12C1"`.

Author(s)

Insang Song

See Also

[calc_modis_par](#)

Examples

```
process_modis_sds(product = "MOD09GA")
```

```
process_modis_swath  Mosaic MODIS swaths
```

Description

This function will return a `SpatRaster` object with values of selected subdatasets. Swath data include curvilinear grids, which require warping/rectifying the original curvilinear grids into rectangular grids. The function internally warps each of inputs then mosaic the warped images into one large `SpatRaster` object. Users need to select a subdataset to process. The full path looks like "HDF4_EOS:EOS_SWATH:{file_path}:mod06:subdataset", where `file_path` is the full path to the hdf file.

Usage

```
process_modis_swath(
  path = NULL,
  date = NULL,
  subdataset = NULL,
  suffix = ":mod06:",
  resolution = 0.05,
  ...
)
```

Arguments

<code>path</code>	character. Full paths of hdf files.
<code>date</code>	character(1). Date to query.
<code>subdataset</code>	character. Subdatasets to process. Unlike other preprocessing functions, this argument should specify the exact subdataset name. For example, when using MOD06_L2 product, one may specify <code>c("Cloud_Fraction", "Cloud_Optical_Thickness")</code> , etc. The subdataset names can be found in <code>terra::describe()</code> output.
<code>suffix</code>	character(1). Should be formatted <code>{product}:</code> , e.g., <code>:mod06:</code>
<code>resolution</code>	numeric(1). Resolution of output raster. Unit is degree (decimal degree in WGS84).
<code>...</code>	For internal use.

Value

- a `SpatRaster` object (`crs = "EPSG:4326"`): if `path` is a single file with full specification of subdataset.
- a `SpatRaster` object (`crs = "EPSG:4326"`): if `path` is a list of files. In this case, the returned object will have the maximal extent of multiple warped layers

Author(s)

Insang Song

See Also

- [process_modis_warp\(\)](#), [stars::read_stars\(\)](#), [stars::st_warp\(\)](#)
- [GDAL HDF4 driver documentation](#)
- [terra::describe\(\)](#): to list the full subdataset list with sds = TRUE
- [terra::sprc\(\)](#), [terra::rast\(\)](#)

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
mod0612_swath <- process_modis_swath(
  path = list.files(
    "./data/mod0612",
    full.names = TRUE,
    pattern = ".hdf"
  ),
  date = "2024-01-01",
  subdataset = "Cloud_Fraction",
  suffix = ":mod06:",
  resolution = 0.05
)

## End(Not run)
```

process_modis_warp *Warp MODIS swath data into rectilinear grid raster*

Description

Swath data is a type of MODIS data, where curvilinear points are stored with varying resolution depending on the relative position of the sensor axis. As this type of data typically does not work well with planar spatial data, users should warp or rectify this data into a rectilinear raster. Main procedure is done with [stars::st_warp](#), in which users are able to customize the threshold to fill potential gaps that appear where the target resolution is finer than the local resolution of curvilinear grid points.

Usage

```
process_modis_warp(
  path = NULL,
  cellsize = 0.1,
  threshold = cellsize * 4,
```

```

    crs = 4326,
    ...
)

```

Arguments

path	File path of MODIS swath with exact sub-dataset specification.
cellsize	numeric(1). Cell size (spatial resolution) of output rectilinear grid raster.
threshold	numeric(1). Maximum distance to fill gaps if occur.
crs	integer(1)/character(1). Coordinate system definition. Should be compatible with EPSG codes or WKT2. See terra::crs and sf::st_crs / EPSG
...	For internal use.

Value

a stars object

Note

This function handles one file at a time.

Author(s)

Insang Song

See Also

[terra::rectify](#)

Examples

```

## NOTE: Example is wrapped in ``dontrun{}`` as function requires a large
## amount of data which is not included in the package.
## Not run:
mod0612_warp <- process_modis_warp(
  path = paste0(
    "HDF4_EOS:EOS_SWATH:",
    list.files(
      "./data/mod0612",
      full.names = TRUE,
      pattern = ".hdf"
    )[1],
    ":mod06:Cloud_Fraction"
  ),
  cellsize = 0.1,
  threshold = 0.4,
  crs = 4326
)

## End(Not run)

```

process_narr	<i>Process meteorological data</i>
--------------	------------------------------------

Description

The `process_narr()` function imports and cleans raw meteorological data, returning a single `SpatRaster` object.

Usage

```
process_narr(  
  date = c("2023-09-01", "2023-09-01"),  
  variable = NULL,  
  path = NULL,  
  extent = NULL,  
  ...  
)
```

Arguments

date	character(2). length of 10 each. Start/end date of downloaded data. Format YYYY-MM-DD (ex. September 1, 2023 = "2023-09-01").
variable	character(1). Variable name acronym. See List of Variables in NARR Files for variable names and acronym codes.
path	character(1). Directory with downloaded netCDF (.nc) files.
extent	numeric(4) or <code>SpatExtent</code> giving the extent of the raster if NULL (default), the entire raster is loaded
...	Placeholders.

Value

a `SpatRaster` object

Note

Layer names of the returned `SpatRaster` object contain the variable acronym, pressure level, and date.

Author(s)

Mitchell Manware

Examples

```
## NOTE: Example is wrapped in \dontrun{} as function requires a large
## amount of data which is not included in the package.
## Not run:
process_narr(
  date = c("2018-01-01", "2018-01-01"),
  variable = "weasd",
  path = "./tests/testdata/narr/weasd"
)

## End(Not run)
```

process_nei

Process road emissions data

Description

The `process_nei()` function imports and cleans raw road emissions data, returning a single `SpatVector` object.

NEI data comprises multiple csv files where emissions of 50+ pollutants are recorded at county level. With raw data files, this function will join a combined table of NEI data and county boundary, then perform a spatial join to target locations.

Usage

```
process_nei(path = NULL, county = NULL, year = c(2017, 2020), ...)
```

Arguments

path	character(1). Directory with NEI csv files.
county	SpatVector/sf. County boundaries.
year	integer(1) Year to use. Currently only 2017 or 2020 is accepted.
...	Placeholders.

Value

a `SpatVector` object

Note

Base files for county argument can be downloaded directly from [U.S. Census Bureau](#) or by using `tigris` package. This function does not reproject census boundaries. Users should be aware of the coordinate system of census boundary data for other analyses.

Author(s)

Insang Song

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
nei <- process_nei(
  path = "./data",
  county = system.file("gpkg/nc.gpkg", package = "sf"),
  year = 2017
)

## End(Not run)
```

process_nlcd	<i>Process land cover data</i>
--------------	--------------------------------

Description

The `process_nlcd()` function imports and cleans raw land cover data, returning a single `SpatRaster` object.

Reads NLCD file of selected year.

Usage

```
process_nlcd(path = NULL, year = 2021, extent = NULL, ...)
```

Arguments

path	character giving nlcd data path
year	numeric giving the year of NLCD data used
extent	numeric(4) or <code>SpatExtent</code> giving the extent of the raster if <code>NULL</code> (default), the entire raster is loaded
...	Placeholders.

Value

a `SpatRaster` object

Author(s)

Eva Marques, Insang Song

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
nlcd <- process_nlcd(
  path = "./data/",
  year = 2021
)

## End(Not run)
```

process_prism

Process PRISM data

Description

This function imports and cleans raw PRISM data, returning a single `SpatRaster` object.
 Reads time series or 30-year normal PRISM data.

Usage

```
process_prism(path = NULL, element = NULL, time = NULL, extent = NULL, ...)
```

Arguments

path	character giving PRISM data path Both file and directory path are acceptable.
element	character(1). PRISM element name
time	character(1). PRISM time name. Should be character in length of 2, 4, 6, or 8. "annual" is acceptable.
extent	numeric(4) or <code>SpatExtent</code> giving the extent of the raster if NULL (default), the entire raster is loaded
...	Placeholders.

Value

a `SpatRaster` object with metadata of time and element.

Author(s)

Insang Song

See Also

[terra::rast](#), [terra::metags](#)

Examples

```
## NOTE: Example is wrapped in \dontrun{} as function requires a large
## amount of data which is not included in the package.
## Not run:
prism <- process_prism(
  path = "../data/PRISM_ppt_stable_4kmM3_202104_nc.nc",
  element = "ppt",
  time = "202104"
)

## End(Not run)
```

process_sedac_codes *Process population resolution code*

Description

Convert full length resolution name to/from resolution code.

Usage

```
process_sedac_codes(string, invert = FALSE)
```

Arguments

string	character(1). Resolution name or code.
invert	logical(1). Default = FALSE. invert = TRUE assumes string provides resolution code, and returns full length resolution.

Value

character

process_sedac_groads *Process roads data*

Description

The process_sedac_groads() function imports and cleans raw road data, returning a single SpatVector object.

Usage

```
process_sedac_groads(path = NULL, extent = NULL, ...)
```

Arguments

path	character(1). Path to geodatabase or shapefiles.
extent	numeric(4) or SpatExtent giving the extent of the raster if NULL (default), the entire raster is loaded
...	Placeholders.

Value

a SpatVector object

Note

U.S. context. The returned SpatVector object contains a \$description column to represent the temporal range covered by the dataset. For more information, see <https://sedac.ciesin.columbia.edu/data/set/groads-global-roads-open-access-v1/metadata>.

Author(s)

Insang Song

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
groads <- process_sedac_groads(
  path = "../data/groads_example.shp"
)

## End(Not run)
```

process_sedac_population

Process population density data

Description

The process_sedac_population() function imports and cleans raw population density data, returning a single SpatRaster object.

Usage

```
process_sedac_population(path = NULL, extent = NULL, ...)
```

Arguments

path	character(1). Path to GeoTIFF (.tif) or netCDF (.nc) file.
extent	numeric(4) or SpatExtent giving the extent of the raster if NULL (default), the entire raster is loaded
...	Placeholders.

Value

a SpatRaster object

Author(s)

Mitchell Manware

Examples

```
## NOTE: Example is wrapped in \dontrun{} as function requires a large
## amount of data which is not included in the package.
## Not run:
pop <- process_sedac_population(
  path = "../data/sedac_population_example.tif"
)

## End(Not run)
```

process_terraclimate *Process TerraClimate data*

Description

The `process_terraclimate()` function imports and cleans climate and water balance data, returning a single SpatRaster object.

Usage

```
process_terraclimate(
  date = c("2023-09-01", "2023-09-01"),
  variable = NULL,
  path = NULL,
  extent = NULL,
  ...
)
```

Arguments

date	character(2). length of 10 each. Start/end date of downloaded data. Format YYYY-MM-DD (ex. September 1, 2023 = "2023-09-01").
variable	character(1). Variable name or acronym code. See TerraClimate Direct Downloads for variable names and acronym codes.
path	character(1). Directory with downloaded netCDF (.nc) files.
extent	numeric(4) or SpatExtent giving the extent of the raster if NULL (default), the entire raster is loaded
...	Placeholders.

Value

a SpatRaster object

Note

Layer names of the returned SpatRaster object contain the variable acronym, year, and month.

TerraClimate data has monthly temporal resolution, so the first day of each month is used as a placeholder temporal value.

Author(s)

Mitchell Manware

Examples

```
## NOTE: Example is wrapped in `dontrun{}` as function requires a large
## amount of data which is not included in the package.
## Not run:
terraclimate <- process_terraclimate(
  date = c("2023-01-01", "2023-01-10"),
  variable = "Precipitation",
  path = "./data/ppt"
)

## End(Not run)
```

process_terraclimate_codes

Process terraClimate variable codes

Description

Convert terraClimate variable names to/from variable codes.

Usage

```
process_terraclimate_codes(string, invert = FALSE)
```

Arguments

`string` character(1). terraClimate variable name or variable code.
`invert` logical(1). Default = FALSE. `invert = TRUE` assumes `string` provides variable code and returns full length variable name.

Value

character

process_tri	<i>Process toxic release data</i>
-------------	-----------------------------------

Description

This function imports and cleans raw toxic release data, returning a single `SpatVector` (points) object for the selected year.

Usage

```
process_tri(
  path = NULL,
  year = 2018,
  variables = c(1, 13, 12, 14, 20, 34, 36, 47, 48, 49),
  extent = NULL,
  ...
)
```

Arguments

`path` character(1). Path to the directory with TRI CSV files
`year` integer(1). Single year to select.
`variables` integer. Column index of TRI data.
`extent` numeric(4) or `SpatExtent` giving the extent of the raster if NULL (default), the entire raster is loaded
`...` Placeholders.

Value

a `SpatVector` object (points) in year `year` is stored in a field named "year".

Note

Visit [TRI Data and Tools](#) to view the available years and variables.

Author(s)

Insang Song, Mariana Kassien

References

<https://www.epa.gov/toxics-release-inventory-tri-program/tri-data-and-tools>

Examples

```
## NOTE: Example is wrapped in ``\dontrun{}`` as function requires a large
## amount of data which is not included in the package.
## Not run:
tri <- process_tri(
  path = "./data",
  year = 2020,
  variables = c(1, 13, 12, 14, 20, 34, 36, 47, 48, 49)
)

## End(Not run)
```

process_variable_codes

Filter gridMET and terraClimate variable names and variable codes

Description

Check user defined variables for gridMET and TerraClimate functions.

Usage

```
process_variable_codes(variables, source = c("gridmet", "terraclimate"))
```

Arguments

variables character(1). Data variables. (Passed from `download_*` or `process_*`).

source character(1). Data source for selected variables ("gridMET" or "TerraClimate").

Value

character

rename_time	<i>Rename \$time</i>
-------------	----------------------

Description

Rename the \$time column of an sftime object.

Usage

```
rename_time(x, newname)
```

Arguments

x	an sftime object
newname	character for new time column name

Value

an sftime object

Author(s)

Eva Marques

sftime_as_mysftime	<i>Convert an sftime to a mysftime</i>
--------------------	--

Description

Convert an sftime object to a mysftime object. x must contain a time-defining column, identified in timename.

Usage

```
sftime_as_mysftime(x, timename)
```

Arguments

x	an sftime object
timename	character: name of time column in x

Value

an sftime object with specific format

Author(s)

Eva Marques

See Also[check_mysftime](#)

sftime_as_sf	<i>Convert an sftime to an sf</i>
--------------	-----------------------------------

Description

Convert an sftime object to an sf object. x must contain a time-defining column, identified in timename.

Usage

```
sftime_as_sf(x, keeptime = TRUE)
```

Arguments

x	an sftime object
keeptime	boolean: TRUE if user wants to keep time column as simple column (default = TRUE)

Value

an sf object

Author(s)

Eva Marques

sftime_as_spatraster	<i>Convert an sftime to a SpatRaster</i>
----------------------	--

Description

Convert an sftime object to a SpatRaster object. Returns a SpatRaster with one layer for each time step in x.

Usage

```
sftime_as_spatraster(x, varname)
```


Arguments

x an sftime object
varname variable to rasterize

Value

a SpatRaster object

Note

Running sftime_as_spatraster can take a long time if x is not spatially structured.

Author(s)

Eva Marques

See Also

[terra::rast](#)

sftime_as_spatrds *Convert an sftime to a SpatRasterDataset*

Description

Convert an sftime object to a SpatRasterDataset object.

Usage

```
sftime_as_spatrds(x)
```

Arguments

x an sftime object

Value

an SpatRasterDataset object

Note

Running sftime_as_spatrds can take a long time if x is not spatially and temporally structured.

Author(s)

Eva Marques

See Also

[terra::sds](#)

sftime_as_spatvector *Convert an sftime to a SpatVector*

Description

Convert an sftime object to a SpatVector object.

Usage

```
sftime_as_spatvector(x)
```

Arguments

x an sftime object

Value

a SpatVector object

Author(s)

Eva Marques

See Also

[terra::vect](#)

sf_as_mysftime *Convert an sf to an sftime*

Description

Convert an sf object to an sftime object. x must contain a time-defining column, identified in timename.

Usage

```
sf_as_mysftime(x, timename)
```

Arguments

x an sf object
timename character: name of time column in x

Value

an sftime object

Author(s)

Eva Marques

 spatraster_as_sftime *Convert a SpatRaster to an sftime*

Description

Convert a SpatRaster object to an sftime object. x must contain a time-defining column, identified in timename.

Usage

```
spatraster_as_sftime(x, varname, timename = "time")
```

Arguments

x	a SpatRaster object
varname	character for variable column name in the sftime
timename	character for time column name in the sftime (default: "time")

Value

a sftime object

Author(s)

Eva Marques

See Also

[terra::rast](#)

 spatrds_as_sftime *Convert a SpatRasterDataset to an sftime*

Description

Convert a SpatRasterDataset object to an sftime object. x must contain a time-defining column, identified in timename.

Usage

```
spatrds_as_sftime(x, timename = "time")
```

Arguments

x a SpatRasterDataset object (~ list of named SpatRasters)
timename character for time column name in the sftime (default: "time")

Value

an sftime object

Author(s)

Eva Marques

See Also

[terra::sds](#)

spatvector_as_sftime *Convert a SpatVector to an sftime*

Description

Convert a SpatVector object to an sftime object. x must contain a time-defining column, identified in timename.

Usage

```
spatvector_as_sftime(x, timename = "time")
```

Arguments

x a SpatVector object
timename character for time column name in x (default: "time")

Value

an sftime object

Author(s)

Eva Marques

See Also

[terra::vect](#)

Index

- * **auxiliary**
 - calc_return_locs, 25
 - check_url_status, 35
 - check_urls, 35
 - generate_date_sequence, 75
 - generate_time_sequence, 75
 - narr_variable, 76
 - process_collection, 80
 - process_gmted_codes, 88
 - process_gridmet_codes, 90
 - process_merra2_time, 95
 - process_sedac_codes, 105
 - process_terraclimate_codes, 108
 - process_variable_codes, 110
- * **spacetime**
 - as_mysftime, 4
 - check_mysf, 34
 - check_mysftime, 34
 - dt_as_mysftime, 74
 - rename_time, 111
 - sf_as_mysftime, 114
 - sftime_as_mysftime, 111
 - sftime_as_sf, 112
 - sftime_as_spatraster, 112
 - sftime_as_spatrds, 113
 - sftime_as_spatvector, 114
 - spatraster_as_sftime, 115
 - spatrds_as_sftime, 115
 - spatvector_as_sftime, 116
- as_mysftime, 4
- base::list.files, 96
- base::regex, 96
- calc_covariates, 5
- calc_covariates(), 15
- calc_ecoregion, 6, 6
- calc_geos, 6, 8
- calc_geos(), 16
- calc_gmted, 6, 9
- calc_gridmet, 6, 10
- calc_hms, 6, 12
- calc_koppen_geiger, 6, 13
- calc_lagged, 14
- calc_merra2, 6, 15
- calc_modis_daily, 17, 18
- calc_modis_daily(), 20
- calc_modis_par, 6, 18, 97
- calc_modis_par(), 18
- calc_narr, 6, 21
- calc_nei, 6, 22
- calc_nlcd, 6, 23
- calc_return_locs, 25
- calc_sedac_groads, 6, 26
- calc_sedac_population, 6, 27
- calc_sedc, 28, 33
- calc_temporal_dummies, 6, 30
- calc_terraclimate, 6, 31
- calc_tri, 6, 32
- check_mysf, 34
- check_mysftime, 4, 34, 112
- check_url_status, 35
- check_urls, 35
- data.frame, 4, 81
- data.table::data.table, 4
- download_aqs, 36, 40
- download_aqs(), 77
- download_cropscape, 37, 40
- download_data, 39, 81, 96
- download_ecoregion, 40, 41
- download_geos, 40, 42
- download_gmted, 40, 44
- download_gridmet, 40, 45
- download_hms, 40, 46
- download_huc, 40, 48
- download_koppen_geiger, 40, 49
- download_merra2, 40, 51
- download_modis, 40, 59

- download_narr, [40, 62](#)
- download_nei, [40, 63](#)
- download_nlcd, [40, 65](#)
- download_prism, [40, 66](#)
- download_sedac_groads, [40, 68](#)
- download_sedac_population, [40, 70](#)
- download_terraclimate, [40, 71](#)
- download_tri, [40, 73](#)
- dt_as_mysftime, [74](#)

- exactextractr::exact_extract, [17–19, 24](#)
- exactextractr::exact_extract(), [24](#)

- future.apply::future_lapply(), [20](#)
- future::plan(), [20](#)

- generate_date_sequence, [75](#)
- generate_time_sequence, [75](#)

- narr_variable, [76](#)
- nhdplusTools::get_huc, [92](#)

- parallelly::availableCores(), [20](#)
- parallelly::makeClusterPSOCK(), [20](#)
- process_aqs, [76, 82](#)
- process_blackmarble, [78, 82](#)
- process_blackmarble(), [18, 20](#)
- process_blackmarble_corners, [78, 79, 79](#)
- process_collection, [80](#)
- process_conformity, [81](#)
- process_covariates, [81](#)
- process_cropscape, [82, 83](#)
- process_ecoregion, [7, 82, 84, 84](#)
- process_flatten_sds, [85](#)
- process_geos, [82, 86](#)
- process_geos(), [8](#)
- process_gmted, [82, 87](#)
- process_gmted(), [10](#)
- process_gmted_codes, [88](#)
- process_gridmet, [82, 89](#)
- process_gridmet(), [11](#)
- process_gridmet_codes, [90](#)
- process_hms, [82, 90](#)
- process_hms(), [12](#)
- process_huc, [82, 91](#)
- process_koppen_geiger, [14, 82, 93](#)
- process_merra2, [82, 94](#)
- process_merra2(), [16](#)
- process_merra2_time, [95](#)

- process_modis_merge, [82, 95](#)
- process_modis_merge(), [18, 20](#)
- process_modis_sds, [85, 97](#)
- process_modis_swath, [82, 98](#)
- process_modis_swath(), [18, 20](#)
- process_modis_warp, [99](#)
- process_modis_warp(), [99](#)
- process_narr, [22, 82, 101](#)
- process_nei, [23, 82, 102](#)
- process_nlcd, [24, 82, 103](#)
- process_prism, [82, 104](#)
- process_sedac_codes, [105](#)
- process_sedac_groads, [27, 82, 105](#)
- process_sedac_population, [82, 106](#)
- process_sedac_population(), [28](#)
- process_terraclimate, [82, 107](#)
- process_terraclimate(), [32](#)
- process_terraclimate_codes, [108](#)
- process_tri, [33, 82, 109](#)
- process_variable_codes, [110](#)

- regexp, [97](#)
- rename_time, [111](#)

- sf, [81](#)
- sf::st_crs, [100](#)
- sf_as_mysftime, [4, 114](#)
- sftime_as_mysftime, [111](#)
- sftime_as_sf, [112](#)
- sftime_as_spatraster, [112](#)
- sftime_as_spatrds, [113](#)
- sftime_as_spatvector, [114](#)
- spatraster_as_sftime, [115](#)
- spatrds_as_sftime, [115](#)
- SpatVector, [81](#)
- spatvector_as_sftime, [116](#)
- stars::read_stars(), [99](#)
- stars::st_warp, [99](#)
- stars::st_warp(), [99](#)

- terra::crs, [100](#)
- terra::describe, [79, 86](#)
- terra::describe(), [99](#)
- terra::freq(), [24](#)
- terra::merge, [79](#)
- terra::metags, [104](#)
- terra::rast, [4, 86, 104, 113, 115](#)
- terra::rast(), [99](#)
- terra::rectify, [100](#)

terra::sds, [4](#), [113](#), [116](#)
terra::sprc(), [99](#)
terra::tapp, [85](#), [86](#), [96](#)
terra::vect, [4](#), [114](#), [116](#)